

ADI-AHS-003

8MP HD AHD/CVI/TVI/CVBS Analog Camera

Features:

- 8MP 4K Resolution, the image is more clear and delicate;
- Zero-latency data transmission, full real-time, high fidelity;
- Long transmission distance, coaxial transmission up to 500 meters;
- Support UTC, not support OSD by the back-end;
- Support coaxial upgrade, version upgrade convenient and efficient;
- Compatible with AHD/TVI/CVI back-end;
- Support XVI/AHD/TVI/CVI/CVBS DVR;
- NTSC&PAL 2 in 1, easy to switch through back-end;
- High-definition quality products with competitive price;

**Parameters:**

Model	ADI-AHS-003
ISP	FH8538E
Sensor	1/3.0 inch GC4653 sensor
Signal format	XVI/AHD/TVI/CVI/CVBS
Video Resolution	PAL/NTSC : 3480(H)x2160(V)
Minimum Illumination	Color:0.05Lux@(F1.2,AGC ON),0Lux with IR Black & White:0.01 Lux@(F1.2,AGC ON),0Lux with IR
W/B Mode	AWB /Manual
Photosensitive Resistance	1 photosensitive resistance interface, support the photosensitive resistor input signal and image, IR-CUT, infrared lamp linkage
Shutter	1/50(1/60) seconds to 1/50,000 seconds
Lens	Built-in 5MP Starlight 2.8mm HD Lens(M12 Lens Mount)
IR LED	4pcs Warm Light/White Light LED
IR Distance	Full Color Night Vision 15Meters
Day and night	Support IR-CUT
Noise reduction	Support 2D-DNR
WDR	Digital WDR
UTC	Support UTC Coaxial Control Up to 500 Meters,Coaxial upgrade
OSD	Optional
Video output	XVI/AHD/TVI/CVI 8MP/5MP/4MP/2MP@15FPS/12.5FPS;CVBS 960H;
Reliability	Comprehensive lightning protection, 7 * 24 hours -10℃~65℃high temperature stable and reliable testing
Material	ABS Plastic Housing
Application	Outdoor(Weatherproof IP66 Standard)
Working Temp.	- 10 ℃ ~ 60 ℃, humidity is less than 90% (no condensation)
Video Setting	Contrast/Sharpness / Saturation /2D-DNR
Video Out	1.0Vp-p, 75Ω Composite, BNC x 1
Power	DC12V±10%
Power Consumption	≤8W
Package Dimension	9*10*10CM
Weight	0.5kgs

