


## Product Specification

<b>Product code(s):</b> Dimmer LUX600-07	
<b>Description:</b> 120V /60Hz, INC 600W / LED 150W / CFL 150W	

Parameter	Symbol	Condition	Min.	Nom.	Max.	Comments	Unit
Input Voltage	VAC		108	120	132		VAC
Frequency	Hz		\	60	\		Hz
Pass Through Current	IAC	120 VAC Nominal	\	5	\		A

Mechanical Requirements							
Parameter	Symbol	Scholium	Min.	Nom.	Max.	Comments	Unit單位
Length	L	\		105.0		\	mm
Width	W	\		53.9		\	mm
Height	H	\		43.4		\	mm
Weight	WT	\		87.8		\	g

Material Requirements		
Part	Quantity (pcs)	Material/Description
Front cover(enclosure) color	1	White, R/G/B: 255/255/255
Rear Cover (enclosure) color	1	Black, R/G/B: 0/0/0
Front Cover	1	R/C Plastics, Lexan 241R
Mounting Yoke	1	aluminium plate, 1.5 mm thicke
Rear Cover	1	R/C Plastics, Lexan 241R
Fastening Screw	2	Galvanized iron
Printed Wiring Board	1	R/C PWB (ZPMV2), FR-4, 94-V0, rated 130 °C.

Application Requirements	
Item	Specification
UL1472 (meets 2015 requirements)	Class A Dimmer (LUX600-02-3 wk)
Accepted Terminal Wire Size	18 gauge
Flammability	Rated V-2 per UL 94
Operating Humidity	30~95%

Regulation Requirements		
Item	Reference Documents	Comments
cULus	UL 1472	

Applicable Markets	
Country List	Comments
United States of America	---
Canada	---

Product Marking Requirements	
Parameter	Description or Reference Document
UL Marking and Labels.	markings as required by UL
Date Code Marking	

If provided, Drawing No. & version level/date \_\_\_\_\_