



ASEP Industrial Electronics Co., Ltd

Tel:+86-757-63379717

Fax:+86 138-2849-4442

E-Mail: timsyblecheung@gmail.com

WebSite:www.asepups.com

No.1 -2, Dongqu 6 Road,

Luocun Lianhe Industrial Area,

Foshan,GuangDong China



Off-Line Series



Our website

Model No:	K500/K1000/TG500/TG1000/MT500/MT1000
Capacity:	6KVA
Place of Origin:	China
Payment Terms:	TT/Negotiable
Shipping Size:	
Weight:	2.8-12 KG
Minimum Order:	1Pcs
Brand Name:	ASEP



ASEP Industrial Electronics Co., Ltd

Item No.	K500	K1000	TG500	TG1000	MT500	MT1000	MT1000S
Series Name	K Series		TG Series		MT Series		
Rated Capacity (with voltage regulated)	500VA/300W	1000VA/600W	500VA/300W	1000VA/600W	500VA/300W	1000VA/600W	1000VA/600W
Input							
Nominal Input Voltage	175VAC-268VAC				162VAC-268VAC		
Fluctuating range	±5%						
Nominal Input Frequency	(45-50)Hz±1Hz						
Output (Battery Mode)							
Nominal Output Voltage	220x(1)VAC		220x(1)VAC		220VAC		
Fluctuating range	±10%						
Nominal Output Frequency	50Hz±1Hz						
Batteries & Runtime							
Battery Type	VRLA						
Battery mounting	Enclosed battery						Extended Battery
Expected Battery Life (years)	1 year~ 3 years						
Battery Capacity	4AHx1PC	9AHx1PC	4AHx1PC	9AHx1PC	7AHx1PC	7AHx2PCS	—
Battery Voltage	12V						
Backup Time	≥5Mins (Halfload)	≥6Mins (Halfload)	≥4.5Mins (Halfload)	≥6Mins (Halfload)	≥5MINS	≥6MINS	—
Transfer Time	≤ 7ms		≤ 8ms		≤7MS		
Physical							
Shipping Weight	2.8KG	6.5KG	2.8KG	6.5KG	6.5KG	15KG	12KG
Shipping Size (mm)	400*200*145	373*220*150	310*205*140	373*220*150	400*200*145	430*240*210	430*240*210
Sockets number	2 pcs	3 pcs	2 pcs	3 pcs	RS-232		
Color	Black		White		Black		
Environmental							
Operating Temperature	0-40°C						
Operating Relative Humidity	10%-90%						
Conformance							
Regulatory Approvals	ISO9001						
Standard Warranty	1 year						