
 Winstars Product Specifications		Version	A0		
		Page	1/1		
Model	WS-UH3049	Date	2016-03-01		
Name	Vertical 4 Ports USB-3.0 Hub Individual Power Switches	Writer	邓文飞		
Picture tuipia 图片		Features: 特点			
		<ol style="list-style-type: none"> Four USB3.0 ports Super-Speed USB3.0 interface support transfer rates up to 5Gbps Max. 2.4A fast charging in sync with data transferring on each port Power On/Off switch for each port Led indicators display the status of each port Backward compatible with USB2.0/ USB1.1 and USB1.0 Support hot swapping, Plug and Play to reach user friendly Over-current /short-circuit design to protect computer safety Supports Microsoft Windows 7/8/10 & MAC 9.1 above/10.2 above 			
Title 标题		Package content 标配			
USB3.0 HUB		SYSTEM REQUIREMENT: 系统配置 Supports Microsoft Windows 7/8/10 & MAC 9.1 above/10.2 above			
Description 介绍		Package content 标配 1 x Vertical 4 Ports USB-3.0 Hub 1 x USB3.0 extension cable 0.8M 1 x DC5V/4A Adapter			
Attractive brushed aluminum finish designed to complement high end Tablet PC/ Laptop or Apple PC products, solid feeling, non-skid rubber feet, compact design with 4 blue LEDs (one per USB port) for diagnosing connectivity. Individual power switch for convenient shut-off of lights and devices. The hub supports USB 3.0 transfer rates up to 5Gbps to allow data to move quickly between devices, ideal for high-throughput devices such as USB external hard drives, flash drives, and USB graphics adapters. Fully plug and play, devices can be hot-swapped, supports USB over-current protection.		SYSTEM REQUIREMENT: 系统配置 Supports Microsoft Windows 7/8/10 & MAC 9.1 above/10.2 above			
Specification 规格					
Hardware 硬件		Functions 功能		Exterior 外观	
Ports	5V DC Jack, Upstream Type-B, Downstream Type-A x 4	Working Standards	USB 3.0 5Gbps Led indicators	Color	Charcoal gray
Button	On/ Off Switch x 4			Cable	80CM AM-BM black
LED	Power Indicator Blue x 4				
Chipset	GL3520-21 (QFN88)				
Flash	PM25LD512	Operating System Support	Windows Mac OS Android Linux		
SDRAM	NIL				
Power Supply	Self power + Power Adapter				
Power Plug	Yes	Max Pixels	NIL		
Power Consumption	<0.5W	Max charging current(A)	2.4A / port		
Rated Voltage/ requency /current	DC 5V/4A Power Adapter				
Dimensions 尺寸		Certification 证书			
Unit Dimensions	114.1*59.1*20.65mm (L x W x H)	CE-EMC	by Request		
Weight	50G	CE-RTTE	by Request		
Housing Material	Aluminum alloy	CE-LVD	by Request		
Shell color	Aluminum alloy Gray	FCC DOC	by Request		
Package Dimensions	** (L x W x H)	FCC ID	by Request		
Environmental 环境		ROHS	by Request		
Operating Temperature	0°C~40°C	Reach	by Request		
Storage Temperature	-10~70°C	3C	by Request		
Relative Humidity(Operational)	10%~90%,noncondensing	Others 其他			
Relative Humidity(Storage)	10%~90%,noncondensing	Method	See Manual		
Drop test (1 Meters)	5 st	Performance	See Test Report		
Cycle work (hours)	24H	Reliability	See Test Report		