

Specification

Model Number	HS-THS-1110	HS-THF-1110
Chipset	Hi3516EV200+IMX307	Hi3516EV200+IMX335
Megapixels	2.0MP	5.0MP
Resolution	1080P/30FPS 1080P/25FPS	2592x1944/15FPS 2592x1520/25FPS
Signal	IP(H.265+)	
Power Supply	DC 12V 2A or POE 48V(802.3AT/AF)Optional	
Operating temperature	-40℃～+60℃	
Consumption	≤10W	
Rotation Range	Medium Speed:Pan:0~220°,Tilt:-45°~40°	
Medium Speed	Pan:0~35°/s, Tilt:0~25°/s	
Auto Flip	NO	
WB	Indoor/Outdoor/Auto/Manual	
IR LED	4pcs 42Mil Array IR Led + 2pcs Laser IR Led (100 Meters)	
Auto Control IR LED	Intelligent Matching Focal Length PWM Dimming Technology	
A-B Scan Range	0-355°	
A-B Scan Speed	1-9 grades	
Preset Points	220pcs presets (dwell time 01-60s interval available)	
Guard Tours	3 groups(each group 16 preset,dwell time and speed select-able)	
Software Control	IE, CMS, Management Platform, P2P	
Stream Code	Support Double Triple Steam Code	
Lens	10X(5.1MM -51MM)	
Video Compression	H.265+/H.265/H.264+/H.264 M-JPEG	
Audio Compression	G711, PCM	
Two Way Audio	Support(Optional)	
Mobile Visit	Support Android、IOS	
Communications Protocol	TCP/IP,HTTP,NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,PPP oE,P2P.....	
Compatible	Support Dahua/Hikvision/XM CMS/Seetong UC....Platform and NVR	
Network Security	HTTPS, 802.1X、IP ADDRESS FILTERING	
Network Interface	1pcs 10/100BaseT WAN, RJ45 Network Port	
Alarm Port	NO	
Quick Command	PELCO Instruction set	
Weatherproof	IP66	
OSD Menu	Support	
Preset Speed Settings	Support	
Power on Mode	Power on /AB scan/horizontal scan/guard position/inspection group 1/ no action	
DNR	2DNR,3DNR	
WDR	≥79dB	

S/N Ratio	≥50dB
Ambient Light Detection	IR illumination on 1-9 grades Selectable
Other Functions	2DNR,3DNR/DWDR/BLC/AGC/WB
Lightning Protection	Transient Voltage 3000V
Single Package	38.5*17.5*14CM/1.67KGS
12pcs Package	57*42*61CM/23KG

Physical Dimension

