

| Model                         |                           |         |         | YSF-09CRDN8     | YSF-12CRDN8     | YSF-18CRDN8     | YSF-24CRDN8  |
|-------------------------------|---------------------------|---------|---------|-----------------|-----------------|-----------------|--------------|
| Nameplate<br>Parameter        | Rated Capacity            | Cooling | W       | 2700            | 3400            | 5300            | 7000         |
|                               | Rated Power Consumption   | Cooling | W       | 820             | 1170            | 1700            | 2300         |
|                               | Rated Running Current     | Cooling | A       | 3.8             | 5.4             | 7.8             | 10.5         |
|                               | Max. Input Power          |         | W       | 1600            | 1600            | 1900            | 2650         |
|                               | Max. Input Current        |         | A       | 8               | 8               | 9               | 14.5         |
|                               | EER Cooling               |         | W/W     | 3.29            | 2.91            | 3.12            | 3.04         |
|                               | Power supply source       |         | V/Ph/Hz | 220-240V-1-50Hz | 220-240V-1-50Hz | 220-240V-1-50Hz | 220~V-1-50Hz |
|                               | Refrigerant               |         |         | R32             | R32             | R32             | R32          |
|                               | Air Flow Volume           |         | m3/h    | 600             | 600             | 850             | 1300         |
|                               | Indoor Noise level        |         | dB（A）   | 41              | 41              | 47              | 49           |
|                               | Outdoor Noise level       |         | dB（A）   | 52              | 52              | 52              | 55           |
|                               | Indoor unit weight (Net)  |         | Kg      | 8               | 8               | 11              | 13.5         |
|                               | Outdoor unit weight (Net) |         | Kg      | 17              | 17              | 23              | 38.5         |
| Indoor unit<br>configuration  | Net Dimension (WxDxH)     |         | mm      | 750×285×200     | 750×285×200     | 900×310×225     | 1082×330×233 |
|                               | Packing Dimension(WxDxH)  |         | mm      | 820×347×277     | 820×347×277     | 970×382×302     | 1155×397×312 |
| Outdoor unit<br>configuration | Compressor                |         |         | HIGHLY          | HIGHLY          | SANYO           | GMCC         |
|                               | Net Dimension (WxDxH)     |         | mm      | 727×456×278     | 727×456×278     | 709x285x535     | 825×655×310  |
|                               | Packing Dimension(WxDxH)  |         | mm      | 760×510×305     | 760×510×305     | 810X330X570     | 945×725×435  |
| Container Loading 40HC        |                           |         | Sets    | 356             | 356             | 252             | 155          |