

hotsale cheap price UTP/FTP/SFTP cat 6 patch cable

Compliance with:

1. ISO/IEC 11801
2. TIA/EIA-568-B.2
3. IEC-60332-1
4. UL 444 (CM/CMR/CMP grade)
5. RoHS

Constuction:

1. Conductor:AWG24/26/28 Stranded BC/CCA/CCS optional
2. Insulation:Solid polyolefin.
3. Cabling:4 twisted pairs cabled Side by side into the cable core.
4. Shielding:Aluminum Mylar Spirally Wrapped(SSTP)

ELECTRICAL PROPERTIES								
Insulation Resistance				Min. 5000 mega ohms-km at 20°C				
Dielectric Test				1000V DC /1 min ; No Breakdown				
Temperature Rating				75°C				
Voltage Rating				30V				
f (MHZ)	Zin-OS (Ohm)	Fitted Z (Ohm)	SRL (dB)	ATT(PATCH) (dB/100M)	DELAY (ns/100M)	MAX. DELAY SKEW(ns/100M)	NEXT (dB)	PSNEXT (dB)
1	100±15	100±15	20.00	1.84	570	45.0	74.3	72.3
4			23.01	3.69	552.00	45.0	65.27	63.27
8			24.52	5.26	546.73	45.0	60.75	58.75
10			25.00	5.89	545.38	45.0	59.3	57.3
16			25.00	7.51	543.00	45.0	56.24	54.24
20			25.00	8.43	542.05	45.0	54.78	52.78
25			24.32	9.47	541.20	45.0	53.33	51.33
31.25			23.64	10.64	540.44	45.0	51.88	49.88
62.5			21.54	15.36	538.55	45.0	47.36	45.36
100			20.11	19.78	537.60	45.0	44.3	42.3
200			18.00	28.97		45.0	39.78	37.78
250			17.32	32.84	536.28	45.0	38.33	36.33