

XIPLE**Zhongshan XIPLE Lighting Co. Ltd (member of FIRST Group)**

www.first-industries.com, Email:jacky.cj@first-industries.com; cellphone/whatsApp: +86-13925383707

DIMMER LED DRIVER SUITED FOR ENERGY SAVING CONTROLLER

S Q	Item with case photo	Bared item picture	Suited for power	MODEL NO.	INPUT	OUTPUT VOLTAGE	OUTPUT CURRENT	OUTLINE SIZE L*W*H mm
1			10-20W	双极隔离 RF4 档调光 CPB1220HFS-RF	AC:170-265V PF \geq 0.95 η \geq 88%	DC:24-42V	DC:250mA ↓ DC:500mA	裸板 81*30.8*19.8 BL-316 外壳 101*36*20.5
2			24-30W	双极隔离 RF4 档调光 CPB2440HFS-RF	AC:170-265V PF \geq 0.95 η \geq 88%	DC:24-42V	DC:600mA ↓ DC:750mA	裸板 89*35.6*20 BL-263 外壳 110.8*41.6*25.8
3			35-40W	双极隔离 RF4 档调光 CBP2440HFS-RF	AC:170-265V PF \geq 0.95 η \geq 88%	DC:24-42V	DC:800mA ↓ DC:1050mA	裸板 89*35.6*20 BL-263 外壳 110.8*41.6*25.8
4			24-40W	双极隔离长条 RF4 档调光 CBP2440HFS-HJRF	AC:170-265V PF \geq 0.95 η \geq 88%	DC:24-40V	DC:600mA ↓ DC:980mA	裸板 149*27.8*17.5 902PC 外壳 170*33*21
5			40-80W	双极隔离一托二 RF4 档调光 CPB80W-40W*2HFS- RF	AC:170-265V PF \geq 0.95 η \geq 88%	DC:24-42V	DC:500mA ↓ DC:1050mA	裸板 152*36.3*23 C23-DG190 外壳 190*42*28.5
6			20-30W	填谷隔离 RF4 档调光 RF-CPB TG2030	AC:170-265V PF \geq 0.88 η \geq 88%	DC:24-42V	DC:500mA ↓ DC:750mA	裸板 91.7*34*22.5 BL-260 外壳 118.8*40*26
7			35-40	填谷隔离 RF4 档调光 RF-CPB TG3040	AC:170-265V PF \geq 0.88 η \geq 88%	DC:24-42V	DC:800mA ↓ DC:1050mA	裸板 91.7*34*22.5 BL-260 外壳 118.8*40*26
8			15-50W	非隔离低 P RF4 档调光 CPB3048LF-RF	AC:170-265V PF \geq 0.5 η \geq 92%	DC:60-200V	DC:140mA ↓ DC:450mA	裸板 81*30.8*18 BL-316 外壳 101*36*20.5
9			15-50W	非隔离低 P RF4 档调光	AC:170-265V PF \geq 0.5	DC:60-200V	DC:140mA	裸板 173*19.3*16.5

				细长条 CPB4050LF-RF	$\eta \geq 92\%$		↓ DC:450mA	BL-长方 15 外壳 207*24*20.5	
10			15-50W	非隔离双极高 P RF4 档调光 不过认证 CPB30-45WHF-RF	AC:170-265V PF \geq 0.95 $\eta \geq 92\%$	DC:60-160V	DC:250mA ↓ DC:310mA	裸板 81*30.8*19.6 BL-316 外壳 101*36*20.5	
11			15-50W	非隔离双极高 P RF4 档调光 能过认证 CPB30-45WHF-RF	AC:170-265V PF \geq 0.95 $\eta \geq 92\%$	DC:60-160V	DC:250mA ↓ DC:310mA	裸板 81*30.8*19.6 BL-316 外壳 101*36*20.5	
12			15-50W	非隔离双极高 P 能过认证 CPB30-45WHF-HJ	AC:170-265V PF \geq 0.95 $\eta \geq 92\%$	DC:60-160V	DC:250mA ↓ DC:310mA	裸板 81*30.8*19.6 BL-316 外壳 101*36*20.5	
13			7-15W	缓启动 DX-CPB015LFA-HQ	AC:170-265V PF \geq 0.5 $\eta \geq 80\%$	DC:24-40V	DC:150mA ↓ DC:350mA	裸板 66.6*39.7*19 DX-82 外壳 100*43*26	
14			7-15W	缓启缓灭 DX-CPB015LFA-HQM	AC:170-265V PF \geq 0.95 $\eta \geq 80\%$	DC:24-40V	DC:150mA ↓ DC:350mA	裸板 89*36.8*22 BL-263 外壳 110.8*41.6*25.8	
15			20-30W	填谷 QH758-OB 24360BTG	AC:170-265V PF \geq 0.88 $\eta \geq 88\%$	DC:24-42V	DC:500mA ↓ DC:750mA	裸板 92.5*30.5*20.8 QH758 外壳 115.8*35.8*23.3	
16			35-40W	双极 QH758 DX-CPB2440HSF	AC:170-265V PF \geq 0.95 $\eta \geq 88\%$	DC:24-42V	DC:800mA ↓ DC:1050mA	裸板 92.5*30.5*20.5 QH758 外壳 115.8*35.8*23.3	
17			35-40W	双极高 P 细长条 DX-CPB2442HSF-CT	AC:170-265V PF \geq 0.95 $\eta \geq 88\%$	DC:24-42V	DC:800mA ↓ DC:1000mA	裸板 210*17.5*13.5 麦拉片 222*19*14	
			120-240W	RF4 档调光 灯带控制器	DC:12-24V	DC:12-24V	DC:10A ↓ DC:20A	成品 120.5*34.7*23.5	
	产品图片			产品型号				外型尺寸 L*W*H mm	
18				手持遥控器三区				外壳 136*42*21.5	

	产品图片			产品型号				外型尺寸 L*W*H mm	
19				RF86 按键型 5 区域 面板节能控制器				86*86*46	
20				信号放大器				铝壳 130.5*74.7*41	
21				RF86 全屏触摸型 6 区域面板节能控制 器				106*86*41	
22				RF200 型 6 区域节 能控制器				200*125*46	