







NOTES:


- 1.Circuit: ON/OFF
- 2.Operation force(Waterproof cap removal): $500 \pm 200\text{gf}$
- 3.Electrical rating: 8A 250VAC U LCUL CQC
15A 125VAC UL CUL CQC
12(6)A 250VAC ENEC
- 4.Contact resistance: $<30\text{m}\Omega$
- 5.Insulation resistance: $>100\text{M}\Omega$
(500VDC between open contacts)
- 6.Dielectric strength: $>1500\text{V}$ 1 minute
- 7.Color: cover is red, body is black.
- 8.Comply with the requitements of the EU directive
2002/95/EC RoHs and subsequent amendments.
- 9.Life:The switch can satisfy the test standard
of BPT0001 and life requirement of all the products.
- 10.Terminal:#187 TAB Terminal,accord the UL310 standard.
- 11.Satisfy the test requirement of PST-11,switch impact.
- 12.Waterproof cap Material PVC GM5075, Yellow card:E96789
- 13.UL file NO:E300970.
- 14.Waterproof cap hardness: $40^{\circ} \pm 10^{\circ}$.
- 15.Glue the waterproof and the switch together. And be sure the
waterproof does not shed when tension strength less than 3KG.
- 16.All Materials Using Meet The Reach Directive.



Panel cut out(Thickness: $1.54 \pm 0.1\text{mm}$)



Circuit of Switch



5	→	10	→	DIMENSIONAL TOLERANCES		APPROVED	CHECKED	DESIGN	DRAWN	ALL SIZE ARE IN	MM		
4	→	9	→	RANGE	TOLERANCE				LMC	SCALE	FIT		
3	→	8	→	X	±0.3					MAT'L	***		
2	增加低铅标准 (REACH)	7	→	X.X	±0.2					MATERIAL NO.		DRAWING NO.	REV
1	增加备注	6	→	X.XX	±0.1								
NO	DESCRIPTION	NO	DESCRIPTION	ANGLES	±0.5°	ROCK TEK ELECTRICAL(SHENZHEN) CO.,LTD.				RT-S02-117-R4NBRC		WIF111003	C

4

3

2

1