

System	Main Processor	Embedded microcontroller Hi3518E
Video	Operation System	Embedded LINUX operation system
	Image Sensor	CMOS 1.0 Megapixel
	Compression	H.264
	Video Standard	PAL
	Picture Resolution	1280*720, 640*480, 320*240 optional
	Video Quality	VGA@25FPS
	Low Illumination	0.1LUX/F1.2
Audio	Code Standards	G.711A
	Audio Input	Built-in 38dB Microphone
	Audio Output	Built-in 8Ω, 1Watt loudspeaker
Recording	Recording Mode	Manual, Calling, Alarm
	Recording Storage	Save in machine TF card
Alarm	Alarm Input	Tamper alarm, wrong password 5 times alarm, Card error 5 times alarm, Magnetic trigger
	Triggle Alarm	Alarm record, snapshot pushed to the phone or tablet
Unlock	Unlock Methods	APP password verify unlock or outdoor station password unlock
Indoor Device	Network	RJ45 interface, 10/100 auto-adaptation
	TF	1 TF card interface
	Wifi	Support 802.11. b/g/n
	Power	DC 15V 1A
	Back up power	1000MAH/ 3.7V
	Power consumption	1.5 W
	Operation Temp.	-40°C-+50°C
	Working condition	IP65
	Installtion	Flush mounted
	Support system	Android, IOS