

DLP VT-08 Projector Specifications		
Portable Intelligent Projector		
Item	Product Characteristic	Product parameters
OPTICS	Display Type	DLP
	Display Chip	TI 0.3 inch WVGA DMD*RGBLED (With Off-axis Ray Machine) >100%
	Brightness	250ANSI / 4500 Lumen
	Lamp	OSRAM LED Lamps
	Uniformity	>90%
	FOFO Contrast Ratio	1000:1
	Standard Resolution	1280x720p
	3D	Support 3D function(DLP-LINK)
PROJECTION	Throw Ratio	1 meter: 39 inches/1.2:1
	Throw Range	20-160 Inch
	Throw Distance	1-6Meter(s)
	Aspect Ratio	4 : 3/16 : 9
	Keystone Correction	Supports automatic and manual
	Projection Methods	Front Projection,Rear Projection,Hanging cast
	Texture of material	Plastic ABS+ electroplating + metal
	Focus mode	Electric motor focusing
	Built-in loudspeaker	8 Ω 5w*2
	Sound effects	Support Dolby sound effect
SYSTEM PARAMETERS	CPU	RK3368 8-core 64Bit A53 1.5Ghz
	Clock Speed	64 bits CPU: Contex A53 Two nuclei GPU: PowerVR G6110 GPU
	Cache	2G DDR3
	RAM	16GB eMMC
	Operating System	Android 6.0.1
	Bluetooth	BT 4.2 (Support external bluetooth Speaker, mouse and gamepad)
	video Support	Real-Time Video Decoder for MPEG-1 MPEG-2 MPEG-4 H263 H264 H265,VC-1,RV
	Audio Support	MP3,WMA,MP2.OGG.ACC.M4A.MA4.FLAC.APE.3GP.WAV
	Photo Support	Supports variety of image formats browsing jpg png bmp etc
	WIFI	2.4G / 5.0G dual-band WIFI
	Remote Control	Infrared remote control and support 2.4g wireless remote control
	Power input parameters	DC 15V IN
	Input support	USB ,IR
ELECTRICAL SPECIFICATION	USB	USB HOST 2.0*2
	TF Card	Maximum supported 32G
	HDMI	Supports HDMI 2.0input
	USB	Able to read data frim USB hard drive support mouse and keyboard access
	Headphone Output	Audio output, 3.5mm connectors (can connect headphones or speakers)
	DC Input	Power adapter: DC 15V3A
	Total Power Consumption	
	Power Performance	AC110-240V,50/60Hz built-in batttery
	Battery life	Standard mode 2H, Bluetooth audio mode 6H
OTHER PARAMETERS	Product Size	172*172*40 mm 0.74 kg
	Package Size	214x214x94 mm
	Package Weight(1set)	1.65kg
	Package Weight(8set/box)	14kg
	Carton Size(8set/box)	445x445X 199 mm