







PAM22



SPECIFICATIONS

Resistive: 16A 250/125VAC Max;

Inductive: 4A 250/125VAC Max;

Degree of protection: IP67;

Contact Resistance: 50mΩ Max. ;

Dielectric Strength: 1500VAC For 1 minute ;

Total Travel: 4±0.5mm ;

Operating Force: 850±200gf ;


Mechanical Life: 300,000 cycles ;

Load Life: 20,000 (Resistive 16A 250VAC) cycles ;


50,000 (Resistive 5A 250VAC) cycles ;

Operating Temperature: -20° C ~ 85° C ;

Function: OFF-ON



Panel Thickness: 6mm MAX.



MATERIAL:

Actuator: SUS ;

Top Base: SUS;

Bottom Base: PA66+GF ;

Terminal: Brass, Silver plated ;

Nut: Brass, Ni plated .

LED Specifications

LED 类型	双向LED灯珠 (交直流通用)	W3	白色	2.8	3.0	3.4	15
寿命	40000小时 (参考值)	U3	蓝色	2.8	3.0	3.4	15
额定电压	AC/DC5-48V	G3	纯绿色	2.8	3.0	3.4	15
额定电流	约10mA	Y2	黄色	1.8	2.0	2.4	15
降压方式	3V灯内置电阻	R2	红色	1.8	2.0	2.4	15
			灯发光颜色 X	最小	一般	最大	额定电流 (mA)
			Emitted color X	顺向电压(V)			

				公差 TOLERANCES		≥30(± 0.5) 5~30(± 0.3) ≤5(± 0.2)		角度 ANGLE ± 5°		单位 DIMENSION UNIT mm.	
				视角 VIEWING ANGLE		比例尺 SCALE	NONE	日期 DATE	2023.11.04	品 名 TITLE	图 号 DRAWING NO
A0	New Issue	2023.11.04	N/A	核 准		核 对		绘 图		PAM22-21Z-F-RXX-S0	
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	APPROVED BY	Richard	CHECKED BY	Sinc	DRAWN BY	ShaoFei Ma	PAM22-21Z-F-RXX-S0	PAM22-21Z-F-RXX-S0_CP_A0