

Specification:

PC model	HD4009		
Motherboard model	Suitable for all DC power 170mm*170m motherboard, port usign with IO plate		
PC size	197mm*197mm*58mm		
Power supply	1*DC_IN	DC head diameter 2.5mm, Support 12V/19V	
CPU	2nd-14th Generation Core,Celeron,Pentium CPU optional		
Memory	DDR3,DDR4 Single double channel Optional, 2G/4G/8G/16G/32G/64G Optional		
Network function	Integrated Realtek 8111E/8111F/8111H Gigabit network Optional		Support network wake-up,Network PXE function
	Integrated Intel i210/i211/i219 Gigabit network Optional		
	Support WIFI/3G/4G, Support external antennae		
Display function	Intel HD Graphics Graphic controller,Support for single display, Dual replication, Dual-Use Extension		
	1*VGA Port		Support for resolution 1920*1080@60Hz
	1*HDMI Port		Optional Support4K Resolution 4096/3840*2160@30Hz
	Optional 1*DP Port		Support4K Resolution 4096/3840*2160@60Hz
USB Function	2*USB3.0	Blue group is USB3.0 speed	
	4*USB2.0	Black group is USB2.0speed	
Serial port Function	1*COM	SupportRS232/RS422/RS485 Optional	
Sound Function	Integrated Realtek ALC662 HD Digital audio decoder,6-channel high-fidelity audio controller		
	1*SPK	Support Audio output	
	1*MIC	Support Microphone input	
	HDMI Port Support HDMI Audio output		
Hard disk Function	2.5inch SSD,HDD,MSATA disk,M.2disk Optional (Capacity 32G to 2TB Optional)		
Switch Function	POWER	Switch button	
Operating environment	Working temperature:-20℃~60℃; Working humidity: 5%~95% Relative humidity, No condensation		
BIOS	AMI BIOS, Support auto power on, Timing boot, Remote boot		
Watch Dog	Watchdog programming, support hardware reset function (256 levels, 0~255 seconds)		
Operating system	Windows 10,Windows 8,Windows 7,Windows XP,Linux etc.		