

Image Sensor	2M Sensor
Still Picture Resolution	Programmable_16MP,12MP,10MP, 8MP,5MP,3MP, 2MP
Photo Imprint/ Stamp	time, date, camera ID, logo,temp
Day/Night Mode	Yes
IR LEDs	40pcs
IR arrange	850nm LED: 15m
Memory	SD Card (8MB – 128 GB)
Sensor FOV angle	55°
Viewing Screen	2寸TFT LCD
PIR Sensitivity	3 sensitive levels: High / Normal / Low
PIR distance	15m – 18m
PIR Angle	105°-120°
Picture Format	JPEG
Video resolution	2.7K(2688x1520),1080P(1920x1080),720P (1280x720), VGA(640x480
Video Format	AVI
Video Length	5sec~2mins. Programmable
Shooting Numbers	1-8 shot burst within 3 seconds
Trigger Time	Within 0.2sec
Trigger Interval	5s-60min
Camera + Video	Yes
Playback Zoom in	2x, 3x, 4x
Device ID	Yes
Time Lapse	Yes
Beep Sound	ON/OFF
SD Card cycle	ON/OFF
Operation Power	Battery: 6V; DC:6V
Battery Type	4~8 AA batteries
External DC	6V
Stand-by Time	4~6 months (4×AA~8×AA)
Auto Power Off	auto switch to mode “ON” in 60s without any operations
Power Consumption	0.15mA-0.3 mA sleep, 200 mA awake, 550mA flash
Low battery Alert	4.8V (4.8V: alert; 4.6V: power off)
PC/ MAC COMPATIBLE	Yes
Interface	USB/SD Card/DC Port
Mounting	Strap; Tripod
Operating Temperature	-10°C to 60°C
Storage temperature	-30 °C to 70°C
Operation Humidity	5%-90%
Waterproof spec	IP54
Dimensions	138x97x83mm
Button definition	A total of 11 buttons, three-position switch OFF/SETUP/ON, MENU button, MODE button, SHOT button, up/down/left/right buttons, OK button
Mode definition	4 modes: video mode/photo mode/playback mode/ settings mode