

Features of OA-68 receipt thermal printer

*Fast printing of text and images *Support network monitor function ,IP change directly from different gateway and QR code *It's built-in power adaptor ,which avoid messy cables everywhere,save space *With wall hanging equipped *It can be used as top paper coming printer and front paper coming printer at the same time	
Model	OA-68
Printing method	Direct thermal printing
Effective printing width	72mm
Resolution	203dpi
Printing speed	USB(200mm/s),USB+Lan (230mm/s),USB+Lan+ Serial /USB+Wifi /USB+BT(260mm/s - 300mm/s)
Printing density	576 dots/line
Character set	Chinese - GB18030
	English, Japanese, Korea etc. custom (contact us for the latest information)
Memory	Input buffer:256k bytes NV Flash :256k bytes
Print font	ASCII Front A - 12x24
	ASCII Front B - 9x17
	Chinese - 24x24
Character per line	Font A - 48 lines
	Font B - 64 lines
	Chinese - 24 lines
Paper width	79.5±0.5mm
Paper roll diameter	Max.Ø 83mm 0.06~0.08mm
Paper loading	Easy paper loading
Paper cut	Auto-cutter
Accessories	Data cable ,power adaptor ,power code,paper roll,CD>manual ,roller,paper separator
Code type	1D - UPC-A/UPC-
	CODE128
	2D - QR code
Interface	USB, USB+Lan, USB+Serial+Lan, USB+Wifi
Individual box	Dimension 27X17X16cm(LXWXH) 1 unit/ carton
Master carton	Dimension 58X37X54cm(LXWXH) 12 units/carton
Dimensions	196(D)x145(W)x135(H)mm
Weight	Net weight :1.2 kg Gross weight :1.7kg
Reliability	Printing head:100KM Cutter :1 million
Emulation	ESC/POS
Driver	Win XP/Vista/Win7/Win8/Win10/Win11/Win 2000/Win CE/OPOS/JPOS
Power supply	Input - AC 100V-240V 50 /60HZ
	Output - DC 24V/2.5A