

Scale drawing/尺寸图

125.0

54.0

27.0

27.0

73.4

27.0

08

06

04

02

01

03

05

07

POWER LED (GREEN)

* METER SEE NOTE 1

L

7±2


Plated Tin

REMOVABLE CLEARANCE HOLE FOR SIGNAL LED LABELS PART #8 SCREW 3PLS (YELLOW) NO. VZ1 (INCLUDED) 8 PLS



Pins/针数	Code/型	Part number("X" is length millimetre mm)/产品料号("X"表示长度, 单位毫米mm)
3pins/3孔	C code/C型	12BOX00011-X

C code 3pins
C型3孔



Pin numbers/针数	3pins/3孔
Rated voltage/额定电压	250V-300V
Rated current(40°C)/额定电流	4.0A and 9.0A
Standards/标准	IEC 61076-2-109
Connector locking system/锁紧方式	Screw-locking/螺丝锁紧
Degree of protection/防护等级	IP67
Wire gauge(mm²)/线规(平方数)	0.14mm²-0.34mm²
Wire gauge(AWG)/线号(平方数)	26AWG-22AWG
Mechanical operation/插拔次数	>100 mating cycles/大于100次
Ambient temperature (operation)/操作温度	-30°C~+80°C
Contact resistance/接触电阻	≤5mΩ
Insulation resistance/绝缘电阻	>100MΩ
Connector body/胶芯	TUP
Pin/端子	Brass and Phosphorus copper with gold plated/黄铜和磷铜镀金
Nut and shell/螺母和铜壳	Brass with nickel plated/黄铜镀镍
Gasket/胶圈	Fluorine ring/氟胶圈
Black glue/黑色胶水	Epoxy resin/环氧树脂
Customs tariff number/海关编码	8544422900
Environmental compliance/环境符合标准	RoHs, Reach

Scale drawing/尺寸图

54 85.0 3" #8 CLEARANCE HOLE * METER
SEE NOTE 1
POWER LED (GREEN)
L 7±2
Plated Tin
J4 J2
J3 J1
SIGNAL LED (YELLOW) 4 PLS
VZ2 SNAP-IN LABELS (INCLUDED)

