

8 "temperature measuring	
Product Model	Category
Camera	Resolution
	Type
	aperture
	Focal length
	White Balance
Screen	Dimensions
	Resolution
	Brightness
System	CPU
	DDR3
	Memory
	Image processing
	Operating system
	Touch screen
Network	Wifi
	Bluetooth
	Ethernet
Accessones	Supplementary Light
	Card reading module (reserved)
	Network module (reserved)
Machine interface	Wigan Interface
	USB interface
	OTG interface
	Serial port 232
	Reset Interface
	Audio
	POE
Temperature measurement module	Thermal imaging
Function	Local offline usage
	Face detection
	1: N face recognition
	1:01
	Stranger testing
	Identification distance recognition
	Remote upgrade of equipment
	Use
	Equipment interface
	Horn
	OSD languages
	Protection level

Conventional parameters	Adapter
	Equipment power
	Working temperature
	Working humidity
	Electrostatic static electricity
	Electromagnetic radiation
	Power consumption
	Installation mode
	Equipment dimensions
	Weight of equipment
	Column aperture

and attendance machine product parameters table

Performance
200W
RGB+ inirared
mm 4.0
M 0-2
Automatic
8 inch, full view IPS LCD screen,Can be customized
1920*1080
400cd/m2
4 cores, RK3288
2GB (optional 4 G)
8GB (optional 16 G, 32G)
Built-in dual ISP
Android 7.1
Optional touch screen
G WiFi2.4
Bluetooth 4.1
10/100 M Netting
Infrared and LED lights
IC/ID card reader, ID card reader
QR code reader, thermal imaging tempera
4G module
Can support Wigan input and Wigan output
USB Host 2.0 1
USB OTG 1 one
One RS232 interface, one WG input, one WG output
Side hole, external key
1 line out Road
Support POE Power Supply (Selection)
Thermal imaging temperature measurement, deviation $\pm 0.3^{\circ}\text{C}$, ranging 80-120 cm
Imaging pixels :32*32
2 W local face bank
Support for simultaneous detection and tracking of 5 individuals
Support 1/100,000 error rate ,99% pass rate
Support optional swipe card module, ID card module can achieve 1:1 face compari
Support
Support
Support
Face recognition、Staff attendance、Temperature measurement、Whether to Wear a
Equipment management, authority management, personnel / photo management, recor etc.
Ω2W 8
English and Chinese multilingual OSD operations
IP64, support waterproof and dustproof, support outdoor use

Power adapter 12 V/1.5A
20W (MAX)
-10°C~+60°C
10~90% relative humidity, no condensation
4K/8K
No frequency exceeding standard
5W MAX
Wall hanging, table support, gate installation, floor support
123.5(wide)*84(thick)*361.3(high) mm
1.5 KG
mm 33

==