

Print	Printing Method	Thermal Line
	Printing Speed	200mm/s
	Resolution	8 dots/mm, 576 dots/line
	Effective Printing	72mm
Character	Character Set	ASCII, GB18030(Chinese),BIG5
	Print Font	Codepage, ANK: 12 x24; Chinese: 24 x 24
	Character per Line	42/48
Paper Spec	Paper Type	Thermal paper
	Paper Width	79.5± 0.5mm
	Paper Roll Diameter	Max:80.0mm
	Roll Core Inner	13mm(min.)
	Paper Thickness	0.06~0.08mm
Paper Supply Method		Drop-in easy paper loading
Reliability	MCBF	60 million lines
	TPH	150km
Barcode		1D: UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128, 2D:PDF417, QR CODE, DATA matrix
Emulation		ESC/POS
Driver		Win98/2000/NT/XP/Vista/Win7/Win8//Win10/LINUX
Interface		USB/USB+Ethernet
Power Supply (Adapter)		AC100 ~240V ± 10%(include) DC 24V, 2A
Auto	Type	Guillotine
	Life	1,500,000 cuts
	Cutting Method	Partial cut
Physical	Net Weight	1.3kg
	Gross Weight	2.3kg
	Printer Dimension (WxLxH)	179 x 152 x 118 mm (L x W x H)
Packing	Inner box size	270*250*175mm, 3kgs
	Outer carton size	8units each carton, 56*53*38cm, 21kgs