

H01B RTOS Specification for Asia Europe Africa Foreign Version

product appearance




Chip Platform & Operating System & Hardware Parameters

chip	ASR3603C	clock rate	832MHZ	architecture	One-core ARM Cortex-R5 processor	audit coun	single-core
system	RTOS	System data type	32 bit	WIFI	NO	GPS	ASR3603C Integration
BT	NO	RAM	16 MB	ROM	16MB	horn	0715 Waterproof Horn
MIC	4015 waterproof and strong anti-interference	motor	Flat motor 0720	SIM card slot	Cato style NANO card holder	Charging method	magnetic attraction
3D hall	0CH1970	G-sensor	QMA6100P	Heart rate/blood oxygen	HX3918	Charging time	2.5H
charging current		Theoretical standby time					

communication frequency band

GSM	GSM: B2 B3 B5 B8	WCDMA	NO
FDD	FDD: B1 B2 B3 B5 B7 B8 B20	TDD	TDD: B34 B38 B39 B40 B41

positioning method							
LBS	LBS base station positioning	GPS	Integrated in CPU	WIFI positioning	YES		
	Accuracy of 100-1000 meters		Accuracy 5-15 meters		YES		
Display screen&touch screen							
fitting method	full lamination	Display screen resolution	240*296	Screen type	LCD	Display screen technology	IPS
Display screen size	2.01						
Touch screen type	capacitive	Touch screen technology	COF	Touch screen appearance effect	2.5D	Touch screen thickness	1.1MM
Touch screen surface technology	Spray fingerprint oil	Touch screen touch point count	single point				
camera							
Camera Pixel	30W	Lens Type	CMOS	module	GC302A		
battery							
Battery Specifications	702833	battery capacity	1050MA/high voltage	type	Polymer lithium battery		
Structural appearance							
Overall Dimensions	53.4*42.55*17.76	weight		color	Blue/Pink/Black/Gold/Grey		
button	Power on/off button: power on/off function return function			whole machine process	APS+PC+spray metal oil+vacuum degree		
				Watch strap craftsmanship	Silicone+Hand feel oil		
APP download QR code							

APP Name	SeTracker2	QR code	
----------	------------	---------	--