



深圳市星光彩科技有限公司
Shenzhen Xing Guang Cai Technology Co.,Limited

Add: No.2505 Songbai Road,Shiyan Town, Bao'an District, Shenzhen, China

Web: www.xgclcd.com

LED Module



pixel pitch	10mm
module size	320*160mm
module resolution	32*16
LED	SMD3535
Scan	1/4scan
Application	Outdoor
Weight	0.42KG
LED chip	Epistar
LED encapsulation mode	Kinglight/Nantionstar

LED Cabinet



Cabinet Size	960*960mm or customized
Cabinet resolution	96*96dots
module quantity	3*6pcs
LED driver	E-energy/Youyi/Chuanglian /Meanwell
Material	Iron
Receiving card	1pcs

LED Screen



Pixel density	10000dots/m ²	Continuous Working Hours	>72 hours
Ave power consumption	300W/m ²	Using Life	100,000 hours
Max power consumption	900W/m ²	MTBF	>10,000H
Optimum Viewing Distance(m)	≥10m	Scatter OOC Point	<0.01%
Brightness(cd/m ²)	≥4500cd	Continuous OOC Point	None
Refresh Rate	1920Hz /s	IP Grade	IP65/IP54
LED Drive mode	Constant Current	Working Temperature	-35C-----+60C
Display color	1M——69G	Working Humidity	10---90%