

SoC	ASR1803S CAT4 / ASR5803W	
Dimension	108*67*16mm	
Bands	LTE FDD B1/3/5/7/8/20/28AB, TDD B38/39/40/41, WCDMA 900/2100MHz (Bands support to be customized)	
Form factor	MIFI	
Battery	Li-ion Battery 2100mAh Working time: 5-6 hrs, Standby time: around 300 hrs (Depend on network)	
Wi-Fi	802.11 b/g/n, WIFI speed up to 867Mbps, max 32 users connection	
DL CA	CA_1A-3A,CA_1A-5A,CA_1A-8A,CA_1A-20A,CA_1A-28A,CA_1C,CA_3A-5A,CA_3A- 7A,CA_3A-8A,CA_3A-20A,CA_3A-28A,CA_3C,CA_5A-7A,CA_7A-8A,CA_7A- 20A,CA_7A-28A,CA_7C,CA_38C,CA_40C,CA_41C	
Data Rates	LTE CAT6 FDD-LTE 300Mbps DL /50Mbps UL	
Hardware	USB	USB2.0, Type C
	SIM	4FF
	LED	Battery/WIFI/Signal/SMS
	Antenna	Build-in FPC type
	Power Voltage	USB DC 5V
Software	Button	Reset, Power,WPS
	Update	FOTA & Local update
	Support OS	Compatible with Windows / MACOS / Linux / Android IPv4/IPv6, SMS, Phonebook, SIM Lock, Firewall, Data statistics,
	Others	WIFI Security
Operation Temperature	Operation Temperature: -10 to 55°C / Operation Humidity: 10% to 80% Storage Temperature: -40 to 85°C / Storage Humidity: 5% to 95%	

Model: L610A

4G LTE Mobile WIFI (MIFI)

ASR1828 LTE Cat6 High Speed Internet Access

Wi-Fi dual Mode, 2*2 MIMO, up to 32 Users