

Specification

Model:	SC08-G
APP:	V380 Pro
System structure:	Embedded Linux system, ARM chip structure
Chip:	KM01N + AIR780E
Resolution:	2+2=4MP
Sensor Resolution:	1/2.9" SC2336*2
Lens:	2*4MM
View angle:	2*80°
Pan-tilt:	Rotates Horizontal:355° Vertical: 90°
Preset point	6
Video compression standard:	H.265/15FPS
Video format:	PAL
Minimum	0.01Lux@ (F2.0, VGC ON),0.Luxwith IR
Electronic shutter:	Auto
Backlight compensation:	Support
Noise reduction:	2D、3D
LED quantity:	Bullet camera: 6pcs white LED + 3pcs Infrared LED PTZ camera: 10pcs Dual Core LED
Network connection:	Suport 4G-SIM card and adapt to RJ45 Network port
Band	B1/3/5/8/38/39/40/41
Night vision	IR-CUT switch Automatic, about 5-8meters (It varies from White Led can be remote control via APP:①Turn ON ②Turn OFF (In automatic mode, the infrared light will be turned ON after dark, it can intelligently detect human body, and Turn ON/OFF the White light in automatic mode)
Audio:	Built-in microphone and speaker, support two-way audio and ADPCM audio compression standard, self-adapt to code stream
Network protocol:	TCP/IP、DDNS、DHCP
Alarm:	①Motion detection and picture push ②AI Human intrusion
Storage:	TF Card (Max 128G) ; Cloud storage /Cloud disk (optional)
Power input:	12V/2A (not including power supply)
Work environment:	Working temperature:-10℃ ~ + 50℃ Working Humidity: ≤95%

environment)
 Turn OFF ③ Auto
 Turn the IR-cut switch to night vision
 intelligently)
 and real-time transmission.
 stream
 Detection
 ial)
 5%RH