

K01X-F Plug Camera



Model:	IK-K01X-F
APP:	V380 Pro
System structure:	Embedded Linux system, ARM chip structure
Chip:	FHM 8626
Resolution:	2MP (1920*1080P)
Sensor Resolution:	CMOS 1/4" SC1345 1920*1080P
Lens	3.6MM
Pan-tilt:	Horizontal: 355° Vertical: 90°
View Angle	80°
Preset point quantity:	6pcs
Video compression standard:	H.265/20FPS
Video format:	PAL
Minimum illumination:	0.02Lux@ (F2.0, VGC ON),0.Luxwith IR
Electronic shutter:	Auto
Backlight compensation:	Support
Noise reduction:	2D、3D
Infrared LED:	6pcs infrared LED
Network connection:	Support WIFI, AP hotspot (without RJ45 Network port)
Network:	Wi-Fi (Support IEEE802.11b/g/ N wireless protocol)
Night Version:	Dual Light switch automatic, 8 Meters (varies from environment)
Audio:	Built-in microphone and speaker, support two-way real-time audio transmission. ADPCM audio compression standard, self-adaptive stream
Network protocol:	TCP/IP、UDP、HTTPDDNS、DHCP、FTP、NTP
Alarm:	①Motion detection, picture push ②Human intrusion Detection (optional) ③ Support connect with 433 Alarm
Storage:	TF Card; Cloud storage (optional)
Connection method:	UK,EU,US Socket (Optional)

Work environment:	Working temperature:-10℃ ~ + 50℃ Working Humidity: ≤95%RH
-------------------	--