



MODEL NUMBER: HCD305 twins phone (2pcs in one giftbox)

Feature:

intercom facility between two phones
call transfer facility from phone 1 to phone 2 and vice versa
privacy during conversation with external party
dual mode FSK/DTMF CLI system compatible
two ways handsfree speaker
3 one touch memory M1 M2 M3
16 digits display big LCD with blue backlight
auto add 0 in call back
display of incoming number, new call, repeat call
checking, erasing for incoming/outgoing calls
28 incoming calls memory
10 outgoing calls memory
predialing and clearing function
5 step LCD contrast adjustable
flash time 80ms, 110ms, 300ms, 600ms and 1000ms
pulse and tone selection
last number redial
pause 1s, 2s, 3s and 4s
3 step ringer volume switchable



MOQ: 1000 SETS (2000pcs)

delivery: 35 to 40 days after get TT or LC copy

price: FOB SHNEZHEN USD22.50/SET (2pcs)

packing: 2pcs per giftbox, 5 sets per carton

carton size: 64.5 x 25.5 x 27.5cm

LCD display description:

10M28D	: Indicate the current month and day (October 28th).
IN	: Displayed when there is call coming and checking incoming call number.
OUT	: Displayed when checking outgoing call numbers.
20	: Indicate the sequence of incoming or out going call during reviewing.
NEW	: Indicate a new incoming call.
REP	: Indicate a repeated call when checking incoming calls.
13:50	: Indicate the current Time.
1234567890	: Display the Incoming or Outgoing call number.
SUN,MON,TUE, WED,THU,FRI,SAT	: Week display.

INSTALLATION

- Plug one end of the power adapter into an electrical outlet & Connect other end of power adapter (out out) in to DC socket provided on phone base

end of power adapter (out put) in to DC socket provided on phone base (Marked DC 9V) on any one phone (phone 1 or phone 2.).

- Plug the line cord (2 Pin) in to the line jack on the base(Marked as TEL LINE) on any (phone 1 or phone 2) one phone and connect other end to the Wall Jack(RJ11).
- Insert one end of 6 core data cord in to the data jack on the base(Marked as DATA) on the phone 1 and connect other end of 6 core data cord in to the 6 Pin Rosette Box.
- Insert one end of another 6 core data cord in to the data jack on the base(Marked as DATA) on the phone 2 and connect other end of 6 core data cord in to the another 6 Pin Rosette Box.
- Interconnect both 6 Pin Rosette Box :

