

产品参数 Specification

灯珠/像素点 Lamp		
序号 Serial Number	项目 Item	P6-6m球形屏 LED Ball
1	封装方式Package Mode	SMD1921
2	物理点间距Pixel Pitch	6mm
3	发光点颜色Pixel Configuration	1R1G1B
模组 LED Module		
序号 Serial Number	项目 Item	P6-6m球形屏 LED Ball
1	模组尺寸（宽x高）Module Size（W*H）	定制 customize
2	模组重量Module Weight	定制 customize
3	模组分辨率（宽x高）Module Resolution(W*H)	定制 customize
4	物理密度Pixel Density	27777点/m²
5	扫描Scsn Mode	8S
6	刷新率 Refresh Rate	3840Hz
7	亮度Brightness	7000CD/m²
8	灰度Signal Processing	16bit
9	接口Port	HUB75
10	模组功耗Power Consumption	定制 customize
11	防护级别 Protection Level	IP65
12	环境温度Temperature	工作温度 Operating: -20℃~70℃ 存储温度Storage: -40℃~85℃
13	相对湿度Relative Humidity	工作Work: 10%~90%, 无凝结No Condensation 存贮Store: 10%~90%, 无凝结No Condensation
箱体 Cabinet		
序号 Serial Number	项目 Item	P6-6m球形屏 LED Ball
1	箱体显示尺寸（宽*高）Screen Area(W*H)	7000mm*7000mm 球形 spherical
2	箱体外观尺寸（宽*高*厚）Cabinet Size(W*H*THK)	7000mm*7000mm 球形 spherical
3	箱体级联 Cascade Cabinet	不支持 not support
4	安装方式 Installation Method	吊装、底座Lifting, base
5	功耗 Power Consumption	平均Average: 150W/m² 最大Max.: 500W/m²