

Programming POS Keyboard KB50M

Specification

Key Number		50 keys
Key Switch Mechanism		Membrane - type Key Switch with 12 million life cycle time
Total Travel Distance		4 + 0.5mm / 2 + 0.6mm
Key Force (Peak Load		60 + 20cN
Interface / Power		USB / +5VDC + 10% / < 100mA
Cable		USB cable stored on the back
Programmable Features		
Programmable Keys		All keys can be programmable
Mufti-Level Programming		support max 4 levels
Time Delay Support		Provide a variable time delay, 0.5 sec per interval
Software Compatibility		Support USB programming in Window ME/ 9X/2K/ XP/7/8/10
Memory		All programmed data are stored in EEPROM, without battery
Magnetic Stripe Card Reader Specification		
Card		Comply with ISO 7812, IBM standards, AAMVA, JIS - 2
Programmable Support		programmable MSR setting for Header, Tailor, Separator, Suffix and Prefix
ISO Card Track	Track 1	210BPI with max 76 characters
	Track 2	210BPI with max 107 characters or 75BPI with max 37 characters
	Track 3	210BPI with max 107 characters
LED		Power MSR and buzzer
Swipe Speed / Head Life - Cycle		10 ~ 180 cm/sec. / 500, 000 swipes
Others		
Electronics Lock		4 section of electronic locks for different level users
Environment	Operating	0°C ~ 50°C(32°F ~ 122°F) , 10% ~ 90% (no condensation)
	Storage	- 20°C ~ 55°C(-4°F ~ 131°F) , 10% ~ 90% (no condensation)
Physical	Dimension	220 (L) x 151 (D) x 40 (H) mm, including MSR / 666 g (N
	Box / Weight	343 (L) x 175 (D) x 55 (H) mm/ 755g (GW)
Accessories		Key cap Puller, 1x & 2x Transparent Caps



Picture

