



Mobile Computer



Android



4G



Wi-Fi



Bluetooth



NFC



1D Barcode



2D Barcode



Camera



GPS

This is a lightweight and portable high-performance mobile computer. With Android 13, octa-core processor, 4-inch touchscreen and 5000mAh removable battery, the excellent configuration delivers highly efficient operation. It supports barcode scanning, NFC, 13MP camera, multiple wireless connections, and features IP67 protection rating, 1.5 meters drop resistance. The mobile computer is thus widely applicable in various fields including warehousing, logistics, retail, finance, transportation, and manufacturing, helping users significantly improve work efficiency.



Specification

Physical Characteristics	
Dimensions	163.5 x 67.0 x 17.1mm/6.44 x 2.64 x 0.67in
Weight	256g / 9.03oz (device with battery)
Display	4-inch, 480 x 800
Touch Panel	Multi-touch panel, gloves and wet hands supported
Power	5000mAh removable battery, support quick charge
Expansion Slot	1 slot for SIM card, 1 slot for SIM or TF card
Interfaces	USB Type-C, USB 2.0, OTG
Sensors	Gravity sensor, distance sensor, light sensor; Gyroscope (optional), geomagnetic sensor (optional)
Notification	Sound, LED indicator, vibrator
Audio	2 microphones, 1 for noise reduction, back; 1 speaker; receiver
Keypad	Main keypad , 2 scan keys, multi-function keys

Performance	
Operating System	Android 13; GMS
CPU	Octa-core, 2.0 GHz
RAM+ROM	4GB + 64GB
Expansion	Supports up to 256GB Micro SD (TF) card

Communication	
WLAN	IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, 5G PA
WWAN	2G: GSM (B2 / B3 / B5 / B8)
	3G: WCDMA (B1 / B2 / B4 / B5 / B8) TD-SCDMA (B34 / B39)
	4G: FDD-LTE (B1 / B2 / B3 / B4 / B5 / B7 /B8 / B12 / B17 / B20 / B28A / B28B) TDD-LTE (B34 / B38 / B39 / B40 / B41)
Bluetooth	Bluetooth 5.0
GNSS	GPS/AGPS, GLONASS, BeiDou, Galileo
Vo-LTE	Support

User Environment	
Operating Temp.	-4 °F to 122 °F / -20 °C to 50 °C
Storage Temp.	-40 °F to 158 °F / -40 °C to 70 °C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.5 m / 4.9 ft. drops to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5 m / 1.64 ft. falls at room temperature
Sealing	IP67 per IEC sealing specifications
ESD	±15 KV air discharge, ±8 KV conductive discharge

Developing Environment	
SDK	Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

Data Collection	
Camera	
Rear Camera	13MP Autofocus with flash
Front Camera	5MP

Barcode Scanning (Optional)	
2D Scanner	Zebra: SE4710; CM60
1D Symbolologies	UPC / EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS etc.
2D Symbolologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX) etc.

NFC	
Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4 cm

Accessories	
Charging base, handle, protective cover, etc	
* For detailed specification, please check Accessory Guide.	