

CEILING SPEAKER

pearller
one more better



Technical data	HSR186-5T	HSR186-6T	HSR186-8T
Load rating	20W	30W	40W
Transformer tapping	20-10-5W	30-15-7.5W	40-20-10W
Frequency range	70-20KHz	50-20KHz	40-20KHz
SPL(@1W/m)	88dB	90dB	92dB
Speaker Ø and Impedance	5 ¼ inch / 8ohms	6 ½ inch / 8ohms	8 inch / 8ohms
Tweeter	½ inch mylar	½ inch mylar	½ inch mylar
Dimension Ø, install depth	Ø186(74) mm	Ø215(80) mm	Ø254(87) mm
Install dimension	Ø161mm	Ø190mm	Ø229mm
Material, Colour	ABS white+black	ABS white+black	ABS white+black



Technical data	HSR186-5C	HSR186-6C	HSR186-8C
Load rating	20W	30W	40W
Frequency range	70-20KHz	50-20KHz	40-20KHz
SPL(@1W/m)	88dB	90dB	92dB
Speaker Ø and Impedance	5 ¼ inch / 8ohms	6 ½ inch / 8ohms	8 inch / 8ohms
Tweeter	½ inch mylar	½ inch mylar	½ inch mylar
Dimension Ø, install depth	Ø186(74) mm	Ø215(80) mm	Ø254(87) mm
Install dimension	Ø161mm	Ø190mm	Ø229mm
Material, Colour	ABS white+black	ABS white+black	ABS white+black