



Standard: VDE0281
Rated Voltage: 300/500V
Max Temp: 70°C

Area (mm ²) 截面积	Conductor导体		Insulation 绝缘体	Sheath 护套	Mean overall平均外径		Minimum insulation resistance at 70°C 70°C时最小 绝缘电阻 MΩ · km
	Construction (NO./mm) 结构	Diam. Of Single (mm) Max. 单支直径	Nom.thick(mm)厚度	Nom.thick(mm)厚度	Lower limit mm 下限	Upper limit mm 上限	
2x0.75	24/0.2	0.21	0.6	0.8	5.7	7.2	0.011
2x1.0	32/0.2	0.21	0.6	0.8	5.9	7.5	0.010
2x1.5	48/0.2	0.26	0.7	0.8	6.8	8.6	0.001
2x2.5	49/0.25	0.26	0.8	1.0	8.4	10.6	0.009
2x4	56/0.3	0.31	0.8	1.1	9.7	12.1	0.007
3x0.75	24/0.2	0.21	0.6	0.8	6.0	7.6	0.011
3x1	32/0.2	0.21	0.6	0.8	6.3	8.0	0.010
*3x1.25	40/0.2	0.21	0.7	0.9	7.6	9.4	0.010
3x1.5	48/0.2	0.26	0.7	0.9	7.4	9.4	0.010
3x2.5	49/0.25	0.26	0.8	1.1	9.2	11.4	0.010
3x4	56/0.3	0.31	0.8	1.2	10.5	13.1	0.009
4x0.75	24/0.2	0.21	0.6	0.8	6.6	8.3	0.011
4x1	32/0.2	0.21	0.6	0.9	7.1	9.0	0.010
4x1.5	48/0.2	0.26	0.7	1.0	8.4	10.5	0.010
4x2.5	49/0.25	0.26	0.8	1.1	10.1	12.5	0.009
4x4	56/0.3	0.31	0.8	1.2	11.5	14.3	0.007
5x0.75	24/0.2	0.21	0.6	0.9	7.4	9.3	0.011
5x1	32/0.2	0.21	0.6	0.9	7.8	9.8	0.010
5x1.5	48/0.2	0.26	0.7	1.1	9.3	11.6	0.010
5x2.5	49/0.25	0.26	0.8	1.2	11.2	13.9	0.009
5x4	56/0.3	0.31	0.8	1.4	13.0	16.1	0.007