

WS2600 offers just the right amount of power for those professional jobs. The powerful 1/3 HP motor produces up to 1200 CFM of airflow making it a great tool for drying surfaces, circulating air, or just ventilation. At only 13kg this machine is lightweight and can be moved with ease while transporting it to different job sites. With the ETL/CETL/CE/SAA safety certification, you can use this machine just about anywhere without the worry of being shocked or harmed in anyway.



Quick disassembly for maintenance



WS2600

A Three speed switch;
Socket and GFCI available



B Lightweight and
Compact Design

C Lowest Current 1.9AMP
for 1/3HP model

D Carpet Clamp

Can be equipped with ADAPTOR



- Underside drying vent
- Quick disassembly for cleaning
- Easy-grip handle
- Stackable for storage



Model	Power		Volume		Speed	Sound Level	Weight	Package Size	Container Quantities (20' / 40' / 40'HQ)	Certification
	HP	Watt	CFM	m ³ /h	m/s	Db	Kg	CM	Units	
WS2600	1/3	250	1200	2020	13.5	63	12	48x43x48	325/675/750	ETL/CE/SAA
	1/2	400	1300	2190	14	65	12	48x43x48	325/675/750	ETL/CE/SAA
	3/4	550	1450	2440	20	68	13	48x43x48	325/675/750	ETL/CE/SAA

C36 produces the **strongest** air flow in its category, equipped with 1 HP(750W) powerful motor. It is the optimal drying machine capable of drying large area in minimum period of time.



C36

The downdraft fan pulls warmer air down and blows it across the entire room. This allows a much more even temperature throughout the drying area. The polyethylene housing is molded to provide 4 drying positions. This downdraft fan features a 6-blade precision pitch fan. Allows 360° directed air flow. Also heavy duty swivel casters for easy mobility. Stacks up to 4 dryers high for storage. Add optional wheel kit and the air mover can be used as a downdraft fan.



With the handle and wheel option, the unit can be easily moved around the job site with "no carrying involved".

Model	Power		Volume		Speed	Sound Level	Weight	Package Size	Container Quantities (20' / 40' / 40'HQ)	Certification
	HP	Watt	CFM	m ³ /h	m/s	Db	Kg	CM	Units	
C36	1HP	750	2200	3700	25	75	16	57x47x53	220/440/525	CE/SAA

Model	Power		Volume		Speed	Sound Level	Weight	Package Size	Container Quantities (20' / 40' / 40'HQ)	Certification
	HP	Watt	CFM	m ³ /h	m/s	Db	Kg	CM	Units	
530	1/4	200	4300	7230	13	70	20	68x58x45	172/352/380	ETL/CE/SAA

510 is a revolutionary series of air mover to the industry that provides super lightweight and long-life operation, maintenance-free performance.

A high quality water proof switch and dual outlet for daisy-chaining multiple units using regular power outlet.

B Easy Wrap Around Cord Design



510



510 can be easily stacked and even can be worked by connecting two blowers.



Here's what 510 provides users:

Super lightweight, large volume flow, long life operation.

Model	Power		Volume		Speed	Sound Level	Weight	Package Size	Container Quantities (20' / 40' / 40'HQ)	Certification
	HP	Watt	CFM	m ³ /h	m/s	Db	Kg	CM	Units	
510	1/4	200	3900	6560	12	70	16	55x36.5x58.5	240/480/604	ETL/CE/SAA

AP110004

If durability and economic is what you are looking for than this is the air mover for you! Made with rolling mold tough LLDPE plastic, AP110004 is meant to endure the wear and tear of any situation. With 1/3rd to 3/4HP(250~550watts) motor and produces up to 1530 CFM of airflow which is the perfect amount to handle most jobs. Have a job in a very wet area? No problem! With the ETL/CETL/CE/SAA safety certification, you can be confident that this machine is safe and will keep you out of harm's way.



AP110005

AP110005 is a durability air mover, made with tough LLDPE plastic, AP110005 is meant to endure the wear and tear of any situation. It has 1/3hp to 3/4hp(250~550w) motor and produces up to 1450 CFM of airflow which is the perfect amount to handle most jobs. With the ETL/CETL/CE/SAA safety certification, you can be confident that this machine is safe and will keep you out of harm's way.



C25

C25 is added with the handle and wheel option, thus the unit can be easily moved around the job site with "no carrying involved".



C18

Equipped with wheels and handles, The C18 features easy mobility.



Model	Power		Volume		Speed	Sound Level	Weight	Package Size	Container Quantities (20' / 40' / 40'HQ)	Certification
	HP	Watt	CFM	m ³ /h	m/s	Db	Kg	CM	Units	
AP110004; C25	1/3	250	1150	1940	18	59	12	47x43x48	325/675/750	ETL/CE/SAA
	1/2	400	1450	2450	22.5	70	12	47x43x48	325/675/750	ETL/CE/SAA
	3/4	550	1530	2570	24	75	13	47x43x48	325/675/750	ETL/CE/SAA

Model	Power		Volume		Speed	Sound Level	Weight	Package Size	Container Quantities (20' / 40' / 40'HQ)	Certification
	HP	Watt	CFM	m ³ /h	m/s	Db	Kg	CM	Units	
AP110005; C18	1/3	250	1200	2020	13.5	63	12	48x43x48	320/665/750	ETL/CE/SAA
	1/2	400	1300	2200	15	68	12	48x43x48	320/665/750	ETL/CE/SAA
	3/4	550	1450	2440	18	68	13	48x43x48	320/665/750	ETL/CE/SAA

C26

C26 is a miniaturized version of professional air movers which are used in many industries including carpet cleaning, sanitation, water damage, and much more. C26 produces 600CFM which is almost 3 times the airflow produces by retail standing fans. It's the perfect garage tool in that it is lightweight, super compact, and can be used in so many ways.



C31

The extra power that this air mover provides makes it perfect for the cleaning industry. This machine is perfect for when you need lots of power but don't want to lug around multiple air movers.



C20



C21



C22

Model	Power		Volume		Speed	Sound Level	Weight	Package Size	Container Quantities (20' / 40' / 40'HQ)	Certification
	HP	Watt	CFM	m ³ /h						
C26	1/10	75	600	1010	12.5	58		40x31x36	654/1335/1536	CE/SAA
C31	1/2	400	1320	2220	22	68		46x44.5x49	300/600/650	CE/SAA
	3/4	550	1400	2350	23	68	13	46x44.5x49	300/600/650	CE/SAA

Model	Power		Volume		Speed	Sound Level	Weight	Package Size	Container Quantities (20' / 40' / 40'HQ)	Certification
	HP	Watt	CFM	m ³ /h						
C20	1/12	65	345	580	11	50	3.5	28x30.5x33.5	1028/2128/2201	CE/SAA
C21	1/2	400	1280	2450	23	65	11	41.5x39.5x49	340/725/870	CE/SAA
C22	1	750	1900	3200	33	70	15	50x47.5x50.5	220/480/600	CE/SAA