

7.0 inch Pole Customer Display HCD70

Features

- 7-inch high brightness IPS LCD, 1024*600 pixels
- Powered by a separate adapter, the work is more stable
- VGA or HDMI interface for optional

Specification

Product Parameter	Interface	VGA or HDMI
	Power Supply	12V 3A
	Horizontal Adjustable Angle	350 Degrees
	Vertical Adjustable Angle	60 Degrees
	Display Cable Length	1.5m
	Power Cable Length	2m
Display Parameter	Display Size	7 inch (Diagonal)
	Display Technology	IPS
	Number of Pixels	1024 Pixels (H)* 600 Pixels (V)
	Active Area	154.2144 mm (H)* 85.92 mm (V)
	Display Ratio	16:9
	Response Time	25ms
	Display Colors	16.7M
	Contrast Ratio	700:1
	Backlight Brightness	430 cd/m ²
Environmental Requirement	Storage Temperature	-20~60 °C
	Work Temperature	-10~45 °C
	Storage Humidity	20%~70%
	Work Humidity	35%~70%
	Power Input	100~240V(50/60Hz)
Unit Packing List	7.0-V (VGA interface)	7.0 -V* 1
		VGA cable* 1
		Power Adapter* 1
		Pole* 2
		Base* 1
	7.0-V (VGA interface) 7.0-H (HDMI interface)	7.0 -H* 1
		HDMI cable* 1
		Power Adapter* 1
		Pole* 2
		Base* 1



Picture

