











CAD FILE:



2.2 UNMATED FORCE: 8 20N INITIAL TEST; 6 20N DURABILITY AFTER TEST

2.3 DURABILITY: 10,000 CYCLES



A12	GND	Ground return	B1	GND	Ground return
-----	-----	---------------	----	-----	---------------

8					TOLERANCE UNLESS SPECIFIED					
7										
6	OUT SRELL	SUS	1	NICKEL50u" MIN.	WITHIN 1.5: ±0.1mm OVER 1.5: ±0.2mm ANGLES: ±2°					
5	BIT	SUS	1	NICKEL30u" MIN.	ISSUE	DATE	DESCRIPTIONS		APPD.	
4	INNER SRELL	SUS	1				UNIT:mm			
3	MID PLATE	SUS	1	NICKEL50u" MIN.			DRWG. NO.:			
2	TERMINAL	C18400	1	NICKEL 50-100u"PLATED. CONTACT AREA:AU 15u".SOLDER AREA:G.F.	MODEL NO: TYPE-C-24P-18. 6 舌头外露1.15 SMT 防水		SCALE:4:1			
1	HOUSING	PA46	1	BLACK			CHK'D	ZHENGZHIHU1		
							APPD.	LILISANJUN		
NO.	DESCRIPTION	MATERIAL		QTY	PLATING		DONGGUAN JINBAOLI ELECTRONICS CO.,LTD			