

Winstars®		Winstars Product Specifications			Version		A0					
					Page		1/1					
		Model		WS-UG39DK3			Date		2014.8.01			
Name		WS-UG39DK3			Writer				chen			
Picture tupia 图片					Features: 特点							
					1.Dock provides SuperSpeed USB 3.0 (5 Gbps) link from PC to Video, Ethernet, MicroPhone In/Earphone, USB 3.0 ports 2 unit , USB 2.0 ports 2 uni and in addition of two USB charging red clour ports 2. HDMI and DVI output supports display resolutions up to 2048x1152 3. Wired Ethernet port supports 10/100/1,000 Mbps speeds 4. USB 3.0 ports backward compatible to USB specification 2.0/1.1 5. USB 2.0 ports backward compatible to USB specification 1.1 6. USB charging ports compatible to BC1.2 specification, red clour ports support fast charge up to 2.4A 7. LED display: Power*1 USB2.0*1 USB3.0*1 USB Charging*2 UGA*1 ports working status 8. DC12V/4A Power Adapter strong enough power supply to devices							
Title 标题												
USB 3.0 Universal docking station												
Description 介绍					Package content 标配			SYSTEM REQUITEMENT: 系统配置				
It is the ideal solution for various work environments that support multiple Laptop standards or where there is the need for a shared workspace. In addition, it is a Ultrabook partners, users will need additional USB ports for all of their necessary peripherals giving you better ergonomics and convenience. It also let IT administrators standardize on one docking station throughout the organization and they're easy for users to understand and user. Docking and undocking is easy. Just plug in the one USB 3.0 cable from these Docking to any USB 3.0 or USB 2.0 port on your Laptop and your display(s) and accessories will be activated in seconds.					1. Dockx1 2. USB A to B 3.0 Extension Cablex1 4. DVI to VGA Adapterx1 5. DC12V/4A Power Adapterx1 6. Installation Driverx1 7. Operation Manualx1			Processor: 2.0Ghz Core2Duo or better RAM: 1GB Recommended Requirements (Full-Screen Video Playback) Processor: Core i5 or i7 2+GHz RAM: 4GB				
Specification 规格												
Hardware 硬件					Functions 功能			Exterior 外观				
Ports		HDMI DVI USB2.0/3.0 Changing port Gigabit DC			Working Standards		USB 3.0 5Gbps Led indicators		Color		black	
Button		NIL							Cable		800MM black	
LED		blue clour led							DC cable		1200mm black	
Chipset		DL3900 VL812B2 FE1.1S										
Flash		8MB			Operating System Support		Windows Mac OS					
SDRAM		DDR3 1GB										
Power Supply		12V4A										
Power Plug		UK/EU/US/China/Australia (option)			Max Pixels		2048*1152					
Power Consumption		1W			Max charing current(A)		NIL					
Rated Voltage/ requency /current		100-240 Va.c. 50/60Hz, 0.1A Max , CLASS II										
Dimensions 尺寸					Certification 证书							
Unit Dimensions		130*103*63 MM (L x W x H)			CE-EMC					NO suitable		
Weight		370G			CE-RTTE							
Housing Material		ABS			CE-LVD							
Shell color		Flat black			FCC DOC							
Package Dimensions		167*126*120 (L x W x H)			FCC ID							
Environmental 环境					ROHS							
Operating Temperature		0°C~40°C			Reach							
Storage Temperature		-10~70°C			3C							
Relative Humidity(Operational)		10%~90%,noncondensing			Others 其他							
Relative Humidity(Storage)		10%~90%,noncondensing			Method		See Manual					
Drop test (1 Meters)		5 st			Performance		See Test Report					
Cycle work (hours)		24H			Reliability		See Test Report					