

PP-12W-UK	Input: 100-240V~ 50-60Hz 0.5A Total Output: 12W(Max) USB-A:5V/2.4A (Max) Color: Black Type: UK plug
PP-20WPDUK	Input:100-240V 50-60Hz 0.5A Output:20W PD Material:ABS,PC Weight: 128g
PP-20WPDEU	Input:100-240V 50-60Hz 0.5A Output:20W PD Material:ABS,PC Weight: 128g
PP-20WPDQCUK	Input:100-240V 50-60Hz 0.5A Output:20W PD+QC3.0 Material:ABS,PC Weight: 128g
PP-20WPDQCEU	Input:100-240V 50-60Hz 0.5A Output:20W PD+QC3.0 Material:ABS,PC Weight: 128g
PP-24W-UK	Input:100-240V~ 50-60Hz 0.8A Total Output: 24W(Max) USB-A: 5V/4.8A (MAX),EACH PORT 2.4A(MAX) Color: Black Type: UK plug
PP-30WPDQCUK	Input:100-240V 50-60Hz 0.5A Output:30W PD+QC3.0 Material:ABS,PC,Aluminum Weight: 136g

PP-30WPDQCUKL	With Lights Input:100-240V 50-60Hz 0.5A Output:30W PD+QC3.0 Material:ABS,PC,Aluminum Weight: 136g
PP-30WPDQCEU	Input:100-240V 50-60Hz 0.5A Output:30W PD+QC3.0 Material:ABS,PC,Aluminum Weight: 116g
PP-30WPDQCEUL	With Lights Input:100-240V 50-60Hz 0.5A Output:30W PD+QC3.0 Material:ABS,PC,Aluminum Weight: 116g
PP-30W GaN-UK	iPhone 14 GaN Charger Model:A2104 Input: 100-240V~ 50-60Hz 1.0A Output Power: 30W (Total) Type-C:5V/3A,9V/3A,12V/2.5A , 15V/2A,20V,1.5A UK Plug Black Color
PP-30W GaN-EU	iPhone 14 GaN Charger Model:A2104 Input: 100-240V~ 50-60Hz 1.0A Output Power: 30W (Total) Type-C:5V/3A,9V/3A,12V/2.5A , 15V/2A,20V,1.5A EU Plug White Color
PP-30W GaN-US	iPhone 14 GaN Charger Model:A2104 Input: 100-240V~ 50-60Hz 1.0A Output Power: 30W (Total) Type-C:5V/3A,9V/3A,12V/2.5A , 15V/2A,20V,1.5A US Plug White Color

PP-38WPDQC-UK	With Lights MODEL:A2203-01 SKU:PP-38WPDQC-UK INPUT: 100-240V~ 50-60Hz 0.8A Output power: 38W (Max) USB-C:5V/3A,9V/3A,12V/3A , 15V/2.5A,20V/1.9A,38W (Max) PPS:3.3V-11V/3A USB-A: 5V/3A,9V/2A,12V/1.5A,18W(Max) USB-C+USB-A:20W+18W UK plug black color
PP-65W GaN-UK	2*Type-C+1*SCP USB-A 65W Max GaN Charger With Lights USB PD AC Adapter 2C+1A Model: A1901 Input: 100-240V ~1.5A 50-60HZ Total Output: 65W(Max) Type-C:5V/9V/12V/15V==3A,20==3.25A PPS: 3.3-11V==5A,3.3-16V==3.8A,3.3-20V==3A USB-A:4.5==5A,5V==4.5A,3.6V-6V==3A, 6V-9V==2A,9V-12V==1.5A UK Plug Black Color
PP-65W GaN-UK(suit)	2*Type-C+1*SCP USB-A 65W Max GaN Charger With Lights USB PD AC Adapter 2C+1A Model: A1901 Input: 100-240V ~1.5A 50-60HZ Total Output: 65W(Max) Type-C:5V/9V/12V/15V==3A,20==3.25A PPS: 3.3-11V==5A,3.3-16V==3.8A,3.3-20V==3A USB-A:4.5==5A,5V==4.5A,3.6V-6V==3A, 6V-9V==2A,9V-12V==1.5A UK Plug Black Color

PP-65W GaN-EU	2*Type-C+1*SCP USB-A 65W Max GaN Charger With Lights USB PD AC Adapter 2C+1A Model: A1901 /A2001 Input: 100-240V ~1.5A 50-60HZ Total Output: 65W(Max) Type-C:5V/9V/12V/15V==3A,20==3.25A PPS: 3.3-11V==5A,3.3-16V==3.8A,3.3-20V==3A USB-A:4.5==5A,5V==4.5A,3.6V-6V==3A,6V-9V==2A,9V-12V==1.5A EU Plug White Color
 PP-65W GaN-US	2*Type-C+1*SCP USB-A 65W Max GaN Charger With Lights USB PD AC Adapter 2C+1A Model: A1901 Input: 100-240V ~1.5A 50-60HZ Total Output: 65W(Max) Type-C:5V/9V/12V/15V==3A,20==3.25A PPS: 3.3-11V==5A,3.3-16V==3.8A,3.3-20V==3A USB-A:4.5==5A,5V==4.5A,3.6V-6V==3A,6V-9V==2A,9V-12V==1.5A USA Plug White Color
 65W2 GaN-UK	Input: 100-240V~ 1.5A 50-60Hz Total Output: 65W(Max) GaN USB-C: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A, USB-A:5V/3A, 9V/3A, 12V/3A, USB-C1+USB-C2 : 45W+20W USB-C1+USB-A : 45W+18W USB-C2+USB-A : 5V/3A USB-1+USB-C2+USB-A : 45W+15W

 PP-100W GaN-UK	Input: 100-240V; 50-60Hz AC USB-C 1 output: PD100W (5V 3A/9V 3A/12V 3A/15V 3A/20V 5A) USB-C 2 output: PD65W (5V 3A/9V 3A/12V 3A/15V 3A/20V 3.25A) USB-A output: QC30W (4.5V 5A/5V 4.5A /9V 3A 12V 2.5A 20V 1.5A)
 PP-100W GaN-EU	Input: 100-240V; 50-60Hz AC USB-C 1 output: PD100W (5V 3A/9V 3A/12V 3A/15V 3A/20V 5A) USB-C 2 output: PD65W (5V 3A/9V 3A/12V 3A/15V 3A/20V 3.25A) USB-A output: QC30W (4.5V 5A/5V 4.5A /9V 3A 12V 2.5A 20V 1.5A) Use three interfaces simultaneously: USB-C1 output: PD65W, C2+A output: 5V 2.6A

 PP-SC010	Shell material: PC flame retardant Conductive metal: copper bar Socket rated current: 13A Socket rated power: 250V@3250W Socket type: UK Number of sockets: 4 bits Line length: 3m Line diameter: 1mm² Switch with overcurrent protection Maximum Absorbed Energy: 700J VPR: 1100V Product size: 30*67*322mm USB output: 5Vdc 2.4Amax USB-A QC: 5V3A/9V2A/12V1.5A USB-C PD: 5V 3A/9V2.22A/12V1.67A Executive standard: BS1363-2 BS62368-1 Total output: MAX 32W
PP-SC011	Shell plastic: PC Conductive metal: phosphor copper, Product weight: 163g Product size: 76*50*56mm Available plugs: UK, Australia, EU, US AC input: 100VAC-250VAC50/60Hz 5USB output: 45W (4USB+1Type-c) USB single port: 5V2.4A (when using USB port, the maximum output of C port is 30W) TYPE-C output: 5V3A 9V2A 12V3A 15V3A 20V2.25A (MAX45W)

PP-SC012	Plastic case: PC Conductive metal: phosphor copper Product weight :126g (bare machine) Product size :68*53*53mm Available plug :UK, AU, EU, US Input :100VAC-250VAC50/60Hz USB-A QC: 5V 3A/9V 2A/12V 1.5A USB-C PD :5V 3A/9V 2.22A/12V 1.67A 20W USB-A+USB-C :5V3A
PP-SC013	20W PD , UK to UK *Power rating: 3750W(250V~15A) *USB input: 250V~50Hz 0.6A *USB-C output: 5V-3A /9V-2.22A/12V-1.67A PD20W *USB-A output:5V-3A /9V-2.22A/12V-1.67A QC18W *USB-C+USB-A output: 5V-3A Max