

Programming POS Keyboard KB60M

Specification

Key Number		60 keys
Key Switch Mechanism		Membrane - type Key Switch with 12 million life cycle time
Total Travel Distance		4 + 0.5mm / 2 + 0.6mm
Key Force (Peak Load		60 + 20cN
Interface / Power		USB: +5VDC + 10% / < 100mA
		PS/2: +5VDC + 10% / < 100mA
Cable		USB cable stored on the back
Programmable Features		
Programmable Keys		All keys can be programmable
Mufti-Level Programming		support max 6 levels
Time Delay Support		Provide a variable time delay, 0.5 sec per interval
True Keyboard Function		Provide true keyboard wedge function, operated with or without the normal
Software Compatibility		Support USB programming in Window ME/ 9X/2K/ XP/7/8/10
Memory		All programmed data are stored in EEPROM, without battery
Magnetic Stripe Card Reader Specification		
Card		Comply with ISO 7812, IBM standards, AAMVA, JIS - 2
Programmable Support		Programmable MSR setting for Header, Tailor, Separator, Suffix and Prefix
ISO Card Track	Track 1	210BPI with max 76 characters
	Track 2	210BPI with max 107 characters or 75BPI with max 37 characters
	Track 3	210BPI with max 107 characters
LED s Indicator / Buzzer		Power, OK and ERROR / Buzzer for MSR
Swipe Speed / Head Life - Cycle		10 ~ 180 cm/sec. / 500, 000 swipes
Others		
Electronics Lock		6 section of electronic locks for different level users
Environment	Operatin g	0℃ ~ 50℃ (32°F ~ 122°F) , 10% ~ 90% (no condensation)
Physical	Storage	- 20℃ ~ 55℃ (-4°F ~ 131°F) , 10% ~ 90% (no condensation)
	Dim. / Weight	254 (L) x 170 (D) x 42 (H) mm / 930g (N.W.)
	Box /	343 (L) x 175 (D) x 55 (H) mm / 1140g (G.W.)

	Weight	
Accessories		RJ45 Y Cable with PS/2 & USB interface, Key cap Puller, 1x and 2x Transparent Caps, Electronic keys

Picture

