

KL-D·III ELECTRICAL OPERATION TABLE

KL-D·III electric operating table is suitable for various operations conducted by medical unit.

Features:

- The bed surface adopts imported carbon plastic plate, the table can be moved vertically which can fulfill the needs of C type arm whole body examination.
- Both sides of the bed rail for the high quality 304 stainless steel.
- The mattress is once foam molded by polyurethane with homogeneous force.
- Various actions are controlled according to electric hydraulic working principle and by remote controller.
- Both alternative and direct current can be used, controlled by CPU with one-key reset function.
- Imported sealing ring and is durable.
- Table support is formed with alloy aluminum by forging process and will never get rusty.
- The base seat and upright column covering are made of high quality 304 stainless steel which can be easily cleaned and sterilized.
- Foot treadle brake device which is easily for moving operating table.

★ Technical Specifications:

Length:2000±100mm

Width:520±20mm

Height Adjustment:(700~1100)±50mm

(Maximum and minimum height of the platform)

Horizontal and longitudinal movement:≥300mm

Back board fold upward:≥70°

Backboard fold downward:≥30°

Forward:≥25°

Backward:≥35°

Leftward and Rightward:≥18°

Head board fold upward:≥50°

Head board fold downward:≥90°

(Leg board fold downward:≥90°

Leg of the board split:≥180°

Waist board lifting:≥100mm

Main Voltage:AC 220±10% 50Hz

Input power:400VA

Accessories:

a pair of shoulder support frame, a pair of arm resting frame,a pair of leg support frame,a screen frame

