



Specification

Outlook	Model	H982 Hunting Camera
 	Features	<ul style="list-style-type: none"> ◆8 Mega pixels Digital Camera ◆4K/10FPS,2.7K/20FPS,1080P/30FPS, video ◆12 months Standby time ◆20m range of IR flash ◆Triggering time: 0.2 Second ◆ 25m triggering distance ◆Spray-water protected(IP protection class66)
	Still image size	32MP(6480x4860P),20MP:5200x3900,16MP:4608x3456,12MP:4000x3000,8M:3264x2448,5M:2592x1944,3M:2048*1536,1M:1280*960
	Video clip	3840x2160/10fps ; 2688x1520/20fps ; 1920x1080/30fps ; 1280x720/60fps ; 1280x720/30fps ; 720x480/30fps ; 640x480/30fps;320x240/30fps
	File format	JPG/AVI
	Lens angle	f=3.3mm; F/NO 2.0; FOV=105; Auto IR filter
	LCD Display	2.4"TFT 720*320
	Memory	External memory(TF card, Class 6 Above, up to 256GB)
	Operation keypad	8 Keys
	The number of IR lamp	40PCS
	Range of IR flash	20m
	Triggering distance	25m (Below 77°F/25°C at the Normal Level)
	PIR sensing angle	85°
	Triggering time	0.2 Second;
	Trigger interval	5sec. - 60min;Programmable
	Shooting numbers	1/2/3/6/10;
	Video Length	3sec-10Minutes.; Programmable
	Effectiveness	Daytime:1m-infinite;Night time:1.5m-20m
	Camera+Video	First take Picture then Video
	Time stamp	On/Off;Include serial No.,temperatureand moon phase
	Time lapse	On/Off; Time Lapse Programmable
	Compressed video	TL Video Time Laps 3 Second ~ 24Hours
	Endless Capture	On/Off
	Target Recording Time1	Time Laps 1 Second ~ 24Hours
	Target Recording Time2	Time Laps 1 Second ~ 24Hours
	Device serial No.	4 digits or 26 alphabets set by yourself
	Build-in Microphone/Speaker	Yes
	Auto-distinguish images	Color images in daytime/black & white night images
	Automatic screen saver	Automatic screen saver in 2 minutes while no keypad controlling
	TV-out	Yes
	PC interface	Mini USB2.0
Power supply	4xAA;Expandable to 8xAA, external 6V power supply,at least 1.5A	
Standby time	approx.12 months	
Lockable	Optional	
Password protection	4-Digit Numbers	
Spray-water protected	Spray-water protected	
Operating temperature	-20℃ to +60℃	
Storage Temperature	-30℃ to +70℃	
Dimensions & Weight	approx.136*90*72mm /	