

4G LTE TDD WIFI Mini IP Camera IP4-404

Features:

- ◆ Metal Pinhole Mini Camera.
- ◆ 4G LTE TDD WIFI Camera.
- ◆ 2.0 Megapixels/5.0 Megapixels.
- ◆ 940nm No Light IR LED:10pcs
- ◆ TF Card Max 128G.
- ◆ Built-in 3MP/5MP 6mm Pinhole Lens.
- ◆ WiFi Switch Button.
- ◆ Support Onvif 2.4.
- ◆ App:Camhi/Camhipro;PC Software:HiP2P.



Key Feature:

- H.265 Video Compression.
- Video Bit-Code:32Kbps~6Mbps.
- Network Protocol:TCP/IP、UDP/IP、HTTP、ICMP、FTP、EMAIL、TELNET.
- Motion Detection:Can set sensitivity 0-100 and detect 4 areas.
- Support Human Shape Recognition,Humanoid Detection.
- Dynamic DNS:LAN & Internet.
- Support IR cut filter with auto switch.
- 4G wireless remote monitoring,support for all 4G SIM card.
- Support Dual-Stream technology.
- Support one channel audio input; one channel audio output;
- Support TF card, 8~128G.
- Support SMART IR, P2P and cross-browser access.
- Provides multi-user hierarchical rights management, allowing multiple users to access the device at the same time.
- Device Power In (DC 12V 2A)

SHENZHEN JBE CCTV CO.,LTD



4G EC200T-EU Frequency Range:

- LTE FDD: B1/B3/B5/B7/B8/B20/B28
- LTE TDD: B38/B40/B41
- WCDMA: B1/B5/B8
- GSM: 900/1800MHz

Product Advantages:

- Offer 3-Years Product Warranties.
- Logistics convenient.
- CCC/CE/FCC Certified.
- Strict product quality control.
- Efficiently working with almost all NVR.
- Lower price.

Product Applications:

This is the best product of safety field. It and hard disk video recorders,cable,power supply,display,etc. Constitute a complete security system. Its application is more extensive. Such as homes,factories,highways,office building,garden,community, or a large public places, etc.

SHENZHEN JBE CCTV CO.,LTD

5/F,Workshop Building A,Tozia Industrial Park,Lezhujiao,

Huangmabu Community,Xixiang Street,Bao'an District,Shenzhen,Guangdong,China

Email:Sales@jbecctv.cn Tel:+86 0755 23037680

www.jbecctv.cn

SHENZHEN JBE CCTV CO.,LTD

Model No.	IP4-THE-404	IP4-THS-404	IP4-THT-404	IP4-THF-404
Sensor	1/2.8" CMOS	1/2.8" SONY	1/2.7" CMOS	1/2.8" SONY
Chip Solution	T31L+SC2335	GK7205V200+307	T31X+SC5238	GK7205V300+IMX335
Resolution	2.0 Megapixels(1080P=1920*1080)		5.0 Megapixels(5MP=2592*1944)	
Frame	20FPS	25FPS	20FPS	15FPS
Illumination	Color 0.0001 Lux@F1.2(AGC on), B&W 0.00 Lux@F1.2(IR on)			
Lens Mount	Built-in 3MP 6mm Pinhole Lens		Built-in 5MP 6mm Pinhole Lens	
IRLED	Built-in 5:10pcs 940nm No Light IR LED			
IR Distance	5~10 Meters(Night Vision)			
Resolution	Main Stream:1920*1080 Sub Stream:640×480/320×240		Main Stream:2592x1944/2560x1440 Sub Stream:800x600/800x448	
Video Bitrate	32Kbps~6Mbps			
Video Processing	H.265+ video coding, support dual stream, AVI format			
	Support 3DNR,Support Digital WDR,Support JPEG Snapshot			
Image Setting	Brightness, contrast, saturation, exposure, up and down inversion, left and right mirror adjustable			
Audio	Audio Input Port Optional			
Network Protocol	TCP/IP,HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, IPv6, IPv4			
Storage	TF Card 8~128G			
Protocol	Support Onvif to NVR			
Motion Detection	4 independent detection areas can be set (sensitivity 1-100 can be set)			
Action with alarm	Send the alarm picture to the designated mailbox; Alarm upload pictures and videos to FTP server			
Sim Card	Support 2G/3G/4G			
Type of network	FDD-LTE, TDD-LTE, WCDMA/HSPA+, TD-SCDMA, GSM/GPRS/EDGE			
Operating Frequency	LTE B1/B3/B8/B38/B39/B40/B41			
	WCDMA 2100/900MHz、TD-SCDMA B34/B39			
	TD-SCDMA B34/B39			
	GSM/GPRS/EDGE: 900/ 1800MHz			
Speed	FDD-LTE/TDD-LTE:UP 50M /Down 150Mbps			
	HSPA+:UP 5.76M /Down 21Mbps			
	TD-SCDMA:UP 2.2Mbps /Down 2.8Mbps			
USIM/SIM	Micro SIM Card			
WIFI Protocol	802.11b/g/n(Max 72Mbps Speed)			
APP	Camhi/CamhiPro			
CMS	HiP2P			

SHENZHEN JBE CCTV CO.,LTD

www.jbecctv.cn

5/F,Workshop Building A,Tozia Industrial Park,Lezhujiao,

Huangmabu Community,Xixiang Street,Bao'an District,Shenzhen,Guangdong,China

Email:Sales@jbecctv.cn Tel:+86 0755 23037680

SHENZHEN JBE CCTV CO.,LTD



Function	Configure by WEB, OSD(on screen display),real-time video transmission, motion detection and IO alarm linkage ,center prompt and picture pop-up after IO alarm; support remote surveillance client software;support mobile monitoring(iPhone, Android).
S/N Ratio	>=50dB
ES	1/50 - 1/10,000S
White Balance	Auto Tracking White Balance
Gamma Ratio	>=0.45
Working Temp.	Outdoor: -40C to +60C
Humidity	0 to 95% RH (non-condensing)
Consumption	450mA
Voltage Input	Power 12V DC 2A
Package Size	10CM*5CM*5CM
Weight	Appro x 0.5kgs

SHENZHEN JBE CCTV CO.,LTD

www.jbecctv.cn

5/F,Workshop Building A,Tozia Industrial Park,Lezhujiao,
Huangmabu Community,Xixiang Street,Bao'an District,Shenzhen,Guangdong,China
Email:Sales@jbecctv.cn Tel:+86 0755 23037680