



- LED

High luminous efficiency COB LED
- Power supply

Flickering free power supply, short circuit and over voltage protection
- Optics

Low glare optic system with PC lens
- Installation

Recessed



Model No.	DSDLR7001-10W	DSDLR9001-20W	DSDLR11001-30W	DSDLR11002-40W
-----------	---------------	---------------	----------------	----------------

Electrical data

Power	10W	20W	30W	40W
Input voltage	200-220V AC or 120-277V AC			
Main frequency	50/60Hz			
Power factor	>0.9			
Total harmonic distortion	<10%			

Photometrical data

Luminous flux	1200lm	2400lm	3600lm	4800lm
Luminous efficiency	120lm/W			
Color temperature	3 CCT			
CRI	>80			
Beam angle	15°, 24°, 36°, 60°			

Material


Optic material	PMMA
Housing material	Aluminum
Product surface finishing	Powder coating

Application

Operating temperature	-40°~ +60°
Operating humidity	10%-90%
IP rate	IP20
Application environment	Intdoor
Dimmable	Optional
Lifespan & Warranty	Lifetime up to 50000H, 5 years warranty

Dimension & Color

Dimension symbol	a	b	a	b	a	b	a	b
Dimension (mm)	70	100	90	110	110	115	110	145



Color option

