


**GALLOP MANUFACTURE CO., LIMITED**

Add: 3F, No.3, Xinglong 2nd Rd, Xiaxu Industrial zone, Changping town, Donguan City, China

Tel: 0769-81175218/81175217 Fax: 0769-81178646 Cell: 86-13128006829

E-Mail :sales2@chinagallop.com web: www.chinagallop.com

M.2 / mSATA series

PRODUCT PICTURE	ITEM NO .	SPEC. DESCRIPTION	Package
	M2-2287	M.2 (NGFF) SSD to USB3.1 Enclosure (TYPE C) JMS580 Compatible with M.2 SATA SSDs. Support SSD disk: 22×30mm/42mm/60mm/80mm NGFF(M.2) interface driver. Data transfer speed of USB 3.1 reaches up to 10 Gbps USB bus powered, no power adapter attached ABS material case A to C cable	Blister package
	M2-2288	ABS M.2 NVMe (PCIe) to USB 3.1 Type-C Enclosure Up to 10Gbps Portable External Case for Solid State Drive Supports NVMe PCIe SSD JMS583 controller chip's GEN2 version, with steady and fast transmission function USB3.1 Type C SSD External Enclosure Suitable for 2230/2242/2260/2280mm Data transfer rate up to 10Gbps for USB 3.1 Plug & Play. A to C cable	Blister package
	M2-RGB	Aluminum M.2 NVMe (SATA + PCIe) to USB 3.1 Type-C Enclosure with RGB Up to 10Gbps Portable External Case for Solid State Drive Supports NVMe PCIe SSD RTL9210B controller chip's GEN2 version, with steady and fast transmission function USB3.1 Type C SSD External Enclosure Suitable for 2230/2242/2260/2280mm Data transfer rate up to 10Gbps for USB 3.1 Plug & Play. A to C cable	Blister package
	M2-2285	M.2 (NGFF) SSD to USB3.1 Enclosure (TYPE C) JMS580 Compatible with M.2 SATA SSDs. Support SSD disk: 22×30mm/42mm/60mm/80mm NGFF(M.2) interface driver. Data transfer speed of USB 3.1 reaches up to 10 Gbps USB bus powered, no power adapter attached Aluminum material case A to C cable	Blister package
	M2-2286	Aluminum M.2 NVMe (PCIe) to USB 3.1 Type-C Enclosure Up to 10Gbps Portable External Case for Solid State Drive Supports NVMe PCIe SSD JMS583 controller chip's GEN2 version, with steady and fast transmission function USB3.1 Type C SSD External Enclosure Suitable for 2230/2242/2260/2280mm Data transfer rate up to 10Gbps for USB 3.1 Plug & Play. A to C cable	Blister package
	M2-2289	M.2 (NGFF) SSD to USB3.1 Enclosure (TYPE C) JMS580 Compatible with M.2 SATA SSDs. Support SSD disk: 22×30mm/42mm/60mm/80mm NGFF(M.2) interface driver. Data transfer speed of USB 3.1 reaches up to 10 Gbps USB bus powered, no power adapter attached Aluminum material case A to C cable	Blister package

	M2-2290	Aluminum M.2 NVMe (PCIe) to USB 3.1 Type-C Enclosure Up to 10Gbps Portable External Case for Solid State Drive Supports NVMe PCIe SSD JMS583 controller chip's GEN2 version, with steady and fast transmission function USB3.1 Type C SSD External Enclosure Suitable for 2230/2242/2260/2280mm Data transfer rate up to 10Gbps for USB 3.1 Plug & Play. A to C cable	Blister package
	M2-2281	M.2 (NGFF) SSD to USB3.1 Enclosure (TYPE C) JMS580 Compatible with M.2 SATA SSDs. Support SSD disk: 22×30mm/42mm/60mm/80mm NGFF(M.2) interface driver. Data transfer speed of USB 3.1 reaches up to 10 Gbps USB bus powered, no power adapter attached Aluminum material case A to C cable	Blister package
	M2-2283	Aluminum M.2 NVMe (PCIe) to USB 3.1 Type-C Enclosure Up to 10Gbps Portable External Case for Solid State Drive Supports NVMe PCIe SSD JMS583 controller chip's GEN2 version, with steady and fast transmission function USB3.1 Type C SSD External Enclosure Suitable for 2230/2242/2260/2280mm Data transfer rate up to 10Gbps for USB 3.1 Plug & Play. A to C cable	Blister package
	M2-2280	M.2 (NGFF) SSD to USB3.0 Enclosure Built-in JMS578 controller Compatible with M.2 SATA SSDs. It is NOT compatible with M.2 PCIe / NVMe SSDs Support SSD disk: 22×30mm/42mm/60mm/80mm NGFF(M.2) interface driver. Data transfer speed of USB 3.0 reaches up to 5 Gbps USB bus powered, no power adapter attached Aluminum material case	Blister package
	MSATA-2242	mSATA SSD to USB3.0 Enclosure Built-in JMS578 controller Support mSATA SSD with maximum capacity of up to 1TB Data transfer speed of USB3.0 reaches up to 5 Gbps USB bus powered, no power adapter attached Aluminum material case	Blister package
	M.2-25	NGFF M.2 to 2.5" SATA III converter Transfer M.2 hard drive to standard 2.5" SATA port Suitable for desktop and laptop PC Works with 2240,2260,2280 M.2 SSD Data transfer rate: 6Gb/s bandwidth Aluminum material case	Blister package

Remark:

1) Price term: EXW

2) Lead Time: 30 days after receipt the deposit.

3) Payment: T/T before shipment.