

Sound Level Meter



Model: SL-5868P

Applications

Widely used to test the sound level of environment, machinery, vehicle, ship and other noise. For industrial environmental protection, construction, health care, teaching and research department.

Specifications

Standards	IEC 651.2, ANSI 1.4.2
Parameters	Lp-Sound Level
Measured	Leq-Equivalent Continuous A Sound Level
	Lmax-Maximum Sound Level
	LN-Percent of All Readings Over Alarm Value Set
Testing	Lp 30~130 dB (A Weighting)
Range	35~130 dB (C Weighting)
	40~130 dB (F Weighting)
	Leq 30~130 dB (10 Seconds, 1 Min, 5 Min, 10 Min, 15 Min, 30 Min, 1 Hour, 8 Hours, 24 Hours)
	LN 0~100%
Resolution	0.1dB
Accuracy	1dB
Frequency	'A' / 'C' / 'F' (Flat)
Time Weighting	Fast (125 ms) / Slow (1 Second)
Microphone	1/2 Inch Electret Condenser Type
Memory	30 Groups with Measuring Conditions
Calibration	94 dB at 1k Hz (sinusoidal)
Frequency Range	20Hz-8kHz
Alarm Value Set	30~130dB
Alarm Output	LED Optional Relay Contact (NC)
Indicator	Low Battery Indicator
Power Supply	4x1.5V AAA Size (UM-4) Battery
External DC	5V, DC, 100mA
Dimensions	236x63x26 mm
Weight	170 g

Features

- * Permits choice 'A', 'C', 'F' weighting and 'Fast' / 'Slow' response times.
- * Offers 4 measurement parameters: Lp (sound level); Leq (Equivalent Continuous A Sound Level); Lmax (Maximum Sound Level) and LN (Percent of all readings over alarm value set).
- * DC output :10 mV/dB. Auto range selection.
- * Can memorize 30 groups of measurements.
- * Use RS-232 data output to connect with PC.
- * Provide Bluetooth data output choice.

Accessories

Standard	Main Unit
Accessories	Windscreen
	Carrying Case(B04)
	Operation Manual
Optional	ND9 Sound Level Meter Calibrator
Accessories	RS-232C Data Cable with Software
	Bluetooth Data Adapter with Software



Sound Level Calibrator



Model: ND9A / ND9B

Applications

For quick and easy calibration of sound level meters and sound measuring systems.

- * Handy sound source for quick and easy calibration of sound level meters and sound measuring systems..
- * The Calibrator employs solid state integrated circuitry that provides accurate and stable performance.
- * Sensitivity calibration of microphones.
- * Suitable for field and laboratory use.

Specifications

Model	ND9A	ND9B
Standards	GB/T15173, ANSI S1.40 CLASS2, IEC942	
Sound Pressure Level	94 dB	94 dB
	114 dB	114 dB
Accuracy	0.5 dB	0.3 dB
Frequency	1000 Hz	
Calibration Of Microphones	1", 1/2"	
Power Supply	1x9V 6F22 Battery	
Dimensions	142x47x47 mm	
Weight	275 g (Including Battery)	

Accessories

Standard Accessories	Main Unit
	Carrying Case(B07)
	Operation Manual

