

4G WIFI Street Light IP Camera IP4-THS-440

Features:

- ◆ Metal & Glass Street Light Camera.
- ◆ 4G LTE TDD WIFI Camera.
- ◆ 2.0 Megapixel 1080P@25FPS.
- ◆ White Light LED:30pcs 30W.
- ◆ Support TF Card Max 128G.
- ◆ Built-in 3MP 2.8mm Fixed Lens.
- ◆ IP65 Weatherproof Standard.
- ◆ Support Onvif.
- ◆ App:Camhi.

Key Feature:

- 1/2.8" SONY CMOS sensor (IMX307), DSP (Hi3516EV200).
- Maximum resolution 1920*1080P@25fps.
- 30pcs White Light LED 15 Meters.
- First 3 hours 100% power for LED, Last 3 hours 50% Power.
- Outdoor Full Color Night Vision Camera.
- Metal body with strong bracket, Glass Panel.
- Built-in 2pcs efficient antennas, 4G & WIFI.
- 3MP 2.8mm HD Fixed Lens, 140° View Degree.
- Support FTP Upload (Pictures & Video).
- 4G wireless remote monitoring, support for all 4G SIM card.
- Support Three-Stream technology.
- Support Alarm upload pictures and videos to FTP Server.
- Support Send the alarm picture to the designated mailbox.
- Support one channel alarm input; one channel alarm output.
- Support Micro SD/SDHC/SDXC card, the maximum up to 128G.
- Support SMART IR, P2P and cross-browser access.
- Mobile APP Name: Camhi.
- CMS: HiP2P for PC.
- Device Power In (DC 12V 2A)



4G Frequency Range:

- Europe: LTE FDD: B1/B3/B5/B7/B8/B20 LTE TDD: B38/B40/B41 WCDMA: B1/B5/B8
- USA: LTEFDD: B2/B4/B5/B7/B8/B12/B17 LTE TDD: B38/B40/B41 WCDMA: B2/B4/B5/B8
- China: LTE FDD: B1/B3/B5/B8 LTE TDD: B34/B38/B39/B40/B41 WCDMA: B1/B5/B8

Product Advantages:

- Offer 3-Years Product Warranties.
- Logistics convenient.
- CCC/CE/FCC Certified.
- Strict product quality control.
- Efficiently working with almost all NVR.
- Lower price.

Product Applications:

This is the best product of safety field. It and hard disk video recorders,cable,power supply,display,etc. Constitute a complete security system. Its application is more extensive. Such as homes,factories,highways,office building,garden,community, or a large public places, etc.

SHENZHEN JBE CCTV CO.,LTD

Model No.	IP4-THS-440
Image Sensor	1/2.8" SONY CMOS Sensor
Resolution	2.0 Megapixels(1080P=1920*1080)
Illumination	Color 0.001 Lux@F1.2(AGC on), B&W 0.00 Lux@F1.2(IR on)
Lens Mount	Built-in 3MP 2.8mm Fixed Lens
IRLED	Built-in 30pcs White Light LED 30W
IR Distance	15M (Full Color Night Vision)
System	PAL / NTSC
Resolution	Main Stream: 1920*1080; Second Stream:1920*960; Third Stream: 640*480,320*240;
JPEG Video Bit-rate	Q720P:640*352;QQ720P:320*176;Special For Mobile Phone View
Frame	2.0MP and below 25fps(50HZ),30fps(60HZ); CBR/VBR adjustable
Video Processing	H.265+ video coding, support dual stream, AVI format; code stream 32~6144kpbs adjustable
	Support 3DNR,Support Digital WDR,Support JPEG Snapshot
Image Setting	Brightness, contrast, saturation, exposure, up and down inversion, left and right mirror adjustable
Network Interface	1*RJ45 Ethernet interface,10/100M self-adaption;
Audio	Built-in Microphone and Speaker
Network Protocol	TCP/IP,HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, IPv6, IPv4
Storage	TF Card (Max 128G)
Protocol	Support Onvif to NVR
Motion Detection	4 independent detection areas can be set (sensitivity 1-100 can be set)
Action with alarm	Send the alarm picture to the designated mailbox; Alarm upload pictures and videos to FTP server
Sim Card	Support 2G/3G/4G
Type of network	FDD-LTE, TDD-LTE, WCDMA/HSPA+, TD-SCDMA, GSM/GPRS/EDGE
Operating Frequency	LTE B1/B3/B8/B38/B39/B40/B41
	WCDMA 2100/900MHz、TD-SCDMA B34/B39
	TD-SCDMA B34/B39
	GSM/GPRS/EDGE: 900/ 1800MHz
Speed	FDD-LTE/TDD-LTE:UP 50M /Down 150Mbps
	HSPA+:UP 5.76M /Down 21Mbps
	TD-SCDMA:UP 2.2Mbps /Down 2.8Mbps
USIM/SIM	Micro SIM Card

SHENZHEN JBE CCTV CO.,LTD

www.jbecctv.cn

5/F,Workshop Building A,Tozia Industrial Park,Lezhujiao,
Huangmabu Community,Xixiang Street,Bao'an District,Shenzhen,Guangdong,China
Email:Sales@jbecctv.cn Tel:+86 0755 23037680

SHENZHEN JBE CCTV CO.,LTD

WIFI Protocol	802.11b/g/n(Max 72Mbps Speed)
APP	Camhi
CMS	HiP2P
Function	Configure by WEB, OSD(on screen display),real-time video transmission, motion detection and IO alarm linkage ,center prompt and picture pop-up after IO alarm; support remote surveillance client software;support mobile monitoring(iPhone, Android).
S/N Ratio	>=50dB
ES	1/50 - 1/10,000S
White Balance	Auto Tracking White Balance
Gamma Ratio	>=0.45
Working Temp.	Outdoor: -20°C to +65°C
Humidity	0 to 95% RH (non-condensing)
Consumption	2800mA
Voltage Input	Power 12V DC 3A
Package Size	56.5X40X13.5 CM
Weight	Appro x 7.0kgs



SHENZHEN JBE CCTV CO.,LTD

www.jbecctv.cn

5/F,Workshop Building A,Tozia Industrial Park,Lezhujiao,
Huangmabu Community,Xixiang Street,Bao'an District,Shenzhen,Guangdong,China
Email:Sales@jbecctv.cn Tel:+86 0755 23037680