


SPECIFICATION:		UL2725 24AWG/2C+28AWG/2C		CONSTRUCTION D.W.G				
RoHS Compliant:	√	Customer's P/N. :						
ITEM		SPECIFICATION						
CONDUCTOR	AWG	24AWG	28AWG					
	Material	bare copper	bare copper					
	COND.Size	11/0.16 (±0.008mm)	7/0.12 (±0.008mm)					
INSULATION	Material	40P PVC/ 80℃	40P PVC/ 80℃					
	AVG.Thick	≥0.20mm	≥0.20mm					
	O.D	1.05±0.05mm	0.80±0.05mm					
	N O.	2c	2c					
Shield	COND.Size	/						
	Coverage	/						
DRAIN	AWG	/						
	COND.Size	/						
Braid Shield	COND.Size	/						
	Coverage	/						
JACKET	AVG.Thick	≥0.50mm						
	Material	50P PVC/ 80℃						
	Color	White						
	O.D	3.50±0.1mm						
				Insulation color				
				24 awg Black, 28 awg Green, 28 awg White, 24 awg Red				
				Marking				
				AWM 2725 E330484 VW-1 80℃ 30V 24AWG/2C+28AWG/2C B&T CABLE c				
				AWM I A FT1 80℃ 30V 24AWG/2C+28AWG/2C -LF-				
				printing color				
ELECTRICAL CHARACTERISTICS				TOC				
1. Rated temperature: 80℃ 2. Rated Voltage: 30V 3. Flame test: pass VW-1/FT1				REV	Date	Change Description		
				BORT		B&T(ZHANGZHOU) CABLE CO.,LTD		
		According to		APPROVED	ROMEN	CUSTOMER		
		UL 1581、UL758		CHECKED	Wang jiao	REV	A	
				DESIGN	FRED	DATE	2020-10-22	
				Specification No.		Customer Appi.	BT2020102202	
UL2725 24AWG/2C+28AWG/2C								