

Specification	Panel Brand	AUO/BOE	AUO/BOE/HKC	LG/BOE/AUO	PANDA/BOE/AUO	CMO/BOE/AUO/COS
	Modle number	LED-2482	LED-3282	LE-4382	LE-5082	LE-5582 (768+8G)
	Screen size	23.6"	32"	43"	49" (50")	55"
	Resolution	1920X1080	2K (1366x768) HD	2K(1920*1080)FHD	2K(1920*1080) FHD	4K (3840*2160) UHD
	Proportion of the screen	16: 9	16: 9	16: 9	16: 9	16: 9
	Backlight type	LED light-emitting diodes	LED light-emitting diodes	LED light-emitting diodes	LED light-emitting diodes	LED light-emitting diodes
	Color classification	black	black	black	black	black
	Border material	plastic	plastic	plastic	plastic	plastic
	Best viewing distance	2.6-3.0M	2.6-3.0M	4.1-5.0M	4.1-5.0M	4.1-5.0M
	The refresh rate	60HZ	60HZ	60HZ	60HZ	60HZ
Image parameters	Viewing Angle	178/178 °	178/178 °	178/178 °	178/178 °	178/178 °
	Scanning way	Progressive scan	Progressive scan	Progressive scan	Progressive scan	Progressive scan
	Receive standard	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC
Function	Network	Ethernet/WIFI	Ethernet/WIFI	Ethernet/WIFI	Ethernet/WIFI	Ethernet/WIFI
	USB media player	USB support video formats: support 1080 p mainstream audio and video decoding, supports MP4, 3 gp, AVI, MPG, RM, RMVB, MOV, MKV, MPEG. USB support audio format: MP3, WMA, AAC The support USB image formats: JPG, JPEG, PNG, BMP				
	Language					
Main interfaces	HDMI interface	1 * HDMI 1.3	1 * HDMI 1.3	1*HDMI 1.3	1*HDMI 1.3	1*HDMI 1.3
	Network interface	1 * network interface	1 * network interface	1 * network interface	1 * network interface	1 * network interface
	USB interface	1 * USB2.0 interface	1 * USB2.0 interface	1 * USB2.0 interface	1 * USB2.0 interface	1 * USB2.0 interface
		1 * start interface	1 * start interface	1*USB3.0 interface	1*USB3.0 interface	1*USB3.0 interface
		2 * video input	2 * video input	2 * video input	2 * video input	2 * video input
	Other interfaces	1 * analog RF interface	1 * analog RF interface	1 * analog RF interface	1 * analog RF interface	1 * analog RF interface
		1 * VGA interface	1 * VGA interface	1 * VGA interface	1 * VGA interface	1 * VGA interface
Power consumption parameters		1 * digital coaxial output interface	1 * digital coaxial output interface	1 * digital coaxial output interface	1 * digital coaxial output interface	1 * digital coaxial output interface
	The power performance	110-220V	110-220V	110-220V	110-220V	110-220V
	The power consumption of the	36W	45W	75W	108W	108W
	Standby power consumption	≤0.5W	≤0.5W	≤0.5W	≤0.5W	≤0.5W
Hardware configuration	The operating system	Android 4.44	Android 4.44	Android 4.44	Android 4.44	Android 4.44
	Packing size		830*125*520mm	1060*150*665mm	1215*150*745mm	1400*150*865mm
	20GP	1020	530PCS	280PCS	200PCS	160PCS
	40HQ	2400	1260PCS	680PCS	500PCS	400PCS
	G.W	3.8KG	5.5KG	11KG	13.5KG	16KG

30-40 days delivery

30% deposit,70% balance need paid before loading.