

SHENZHEN HUARUI ELECTRONIC TECHNOLOGY CO., LIMITED

Floor 5,Building B,New Retail Digital Industrial Park,Nanchang Second Industrial Zone,Xixiang Street,
Bao'an District,Shenzhen,Guangdong

Mobile:0086-137 2429 2138 Email:alex@szhret.com Wechat/Skype/Whatsapp:+86 137 2429 2138



H1101 Android 10.1 inch Pos Terminal Spec

CPU	Quad core CPU,1.8GHZ,RK3566,64 bits,A55 Processor
Operation System	Android 11
DDR	2GB
Nand Flash	8GB EMMC(MAX 64)
LCD	10 inch,1024*600 resolution
Touch Screen	Capacitive multi-touch screen
Camera QR Code Scanner	0.3MP camera with LED flash and fixed-focus
Magnetic Stripe reader (Optional)	Supports triple track (tracks 1/2/3), bi-directional
IC Card Reader(optional)	Comply with ISO7816 standards
NFC Card Reader(Optional)	13.56MHZ ISO/IEC 14443 TYPE A/B. Mifare card read and write
SIM Slot	1 SIM Slot
Thermal printer	High-speed thermal printer,58mm printing paper width,40mm paper roll diameter
4G module	Default LTE-FDD B1/B3/B8,LTE-TDD B38/B39/B40/B41,compatible with 3G/2G,different module can support different bands
WIFI	Comply with IEEE802.11b/g/n
Bluetooth	BT 4.0
USB Port	USB 2.0 HOST*1,USB 2.0 Device*1
OTG Port	MINI USB OTG*1
RS232 Port	Standard DB9 serial port*1
RJ11 Port	Cash drawer port*1,Pinpad pos port*1
RJ45 Port	Ethernet port*1
SD slot	1 slot,Max 32 GB

Packing

Packing	Standard industrial packing
Adapater	Input 100-240V power output DC 9V,5A
Battery	7.4V,2000mAh(5000mAh optional) Li-chargable battery
Weight	2.5KG
Dimension	320*259*80MM