

SPECIFICATION

MODEL	MSL948/ZL948	Metric Units
ENGINE	Engine Model	Weichai Deutz 6102
	RPM	2400
	Rated Power	92 kW
	Emissions	EU Stage II
WEIGHTS	Operating Weight	7660 kg
	Rated Load	2800-3000 kg
BUCKETS	Bucket Capacities	1.7 m ³
TRANSMISSION	Max. Travel Speed	45 km/h
	Gear Box	CVT 315 split torque converter
	Axle	30 #
	Axle Base	2700 mm
	Brake	Air Brake
HYDRAULIC SYSTEM	Hydraulic Cycle time - lift	≤ 10 s
DIMENSIONS(APPROXIMATE)	Min. Ground Clearance	500 mm
	Wheel Base	2100 mm
	Reach at Max.Dump Height	3600 mm
	Dump Reach	1200 mm
	Overall Length - With Bucket	6750 mm
	Overall Width	2400 mm
	Overall Height	3150 mm
OPERATING SPECIFICATIONS	Tyre Size	17.5-25
	Joystick	Machanical
	Min. turning radius	4500 mm
STANDARD EQUIPMENT	Hour meter	Yes
	Tool Box	Yes
	Dual Hight&Low Speed Handle	Yes
OPTIONAL EQUIPMENT	Air Conditioning/heater	Option
	Quick Change	Option
	Multifunctional Attachment	Option
	Hydraulic Pilot	Option
	Extended Lifting Arm	4.8m Dump Height
	Engine Cover	Electrical Upturned