



Model:	SQ001-G
APP:	V380 Pro
System structure:	Embedded Linux system, ARM chip structure
Chip:	KM01D
Resolution:	2+2=4MP
Sensor Resolution:	1/2.9" MIS2008*2
Lens:	4MM
View angle:	2*80°
Pan-tilt:	Rotates Horizontal:355° Vertical: 90°
Preset point quantity:	6
Video compression standard:	H.265/15FPS
Video format:	PAL
Minimum illumination:	0.01Lux@ (F2.0, VGC ON),0.Luxwith IR
Electronic shutter:	Auto
Backlight compensation:	Support
Noise reduction:	2D、3D
LED quantity:	Bullet camera: 4pcs Dual LED PTZ camera: 4pcs white LED + 4pcs Infrared LED
Network connection:	Support 4G-SIM card
Frequency Band	LTE-FDD:B1/3/5/8 LTE-TDD:B38/39/40/41
Night vision	IR-CUT switch Automatic, about 5-8meters (It varies from environment) White Led can be remote control via APP:①Turn ON ②Turn OFF ③ Auto (In automatic mode, the infrared light will be turned ON after the IR-cut switch to night vision auto , it can intelligently detected human body, and Turn ON/OFF the White light intelligently.)
Audio:	Built-in microphone and speaker, support two-way audio and real-time transmission. ADPCM audio compression standard, self-adapt to code stream
Network protocol:	TCP/IP、UDP、HTTP、DDNS、DHCP、FTP、NTP
Alarm:	①Motion detection ,Voice Alarm,picture push ② Free AI Human Motion Detection
Storage:	TF Card (Max 128G) ; Cloud storage /Cloud disk (optional)
Power input:	12V/2A (Including power supply)
Work environment:	Working temperature:-10℃ ~ + 50℃ Working Humidity: ≤95%RH