

Product name	OA-48		
Print Method	Direct Thermal		
Print Speed	260~300mm/s(USB+Lan +Serial port)		
Resolution	576dots/line or 572dots/line		
Printing Width	72mm		
Paper separator(option)	48mm/52mm/56mm/64mm/68mm/76mm/80mm		
Interface	USB+Lan/ USB+Serial/ USB+Serial+Lan/ USB+Serial+Lan+BT/USB+wifi for optional		
Page Mode	Support		
Input buffer	256kbytes		
NV Flash	256kbytes		
Font A	12x24		
Font B	9x17		
Chinese	GB18030,BIG5 24x24dots		
Japanese/Korea	Support		
User-defined	Support		
Power , Paper,Erro	Support		
Hanging device	Equipped		
1D	UPC-A/UPC-		
Sensors	Paper out, paper near end, cover open, cutter jam,paper jam and black mark detection(Optional)		
Input	AC 100V-240V 50/60HZ		
Output	DC 24V/2.5A		
Paper Type	Thermal Receipt Paper		
Paper Width	48mm/52mm/56mm/64mm/68mm/76mm/80mm		
Paper Thickness	0.06~0.08mm		
Roll Dia	Max. Ø 83 mm		
Paper Load	Easy paper loading		
Paper Cut	Manual tear or Auto-cutter		
Working Condition	0°C~45°C, 10%~80%RH		
Storage Condition	-10°C-60°C,10%~90%RH		
Dimensions	191(D)x146(W)x129(H)mm		
Net weight	1.94kg	Gross	2.14kg
Printing head	150KM		
cutter	1.5million		
	data cable,power adaptor,power code,paper		
Master carton	Dimension	12units/carton	
Emulation	ESC/POS		
Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win11/CE/OPOS/JPOS		
SDK	Android, IOS		

