



Waterproof Resistance	IP68
Screen Size	1.96"
Screen Material	AMOLED
Screen Cover	3D Glass Cover
Middle Frame	Zinc alloy
Bottom shell Material	PC
Button	aluminium alloy
Wristband	solid Silicone
Buckle	solid Silicone
Tongue clasp	Stainless Steel
Bare Metal weight(With Band)	
Body Size(L x W x H)mm	53*38.4*10.4mm
Product with Package Weight	TBD
Hardware	
CPU	RL8763EWE-VP
BT	RL8763EWE-VP
G SENSOR	STK8321
PPG Heart rate sensor	VC9202(VP60A2)
Speaker	0815(IP68)
Microphone	4015
Touch chips	CHSC5816NEW
Screen	ONCELL
Screen Resolution	410*502
Flash	128Mb Nor Flash
Bluetooth	BLE5.2
Power	
Battery Capacity	300mAh
Standby	About 8days
BT standby	3~5days (BT calling)
Type of Battery	Polymer lithium battery

Charging Method	Magnetic charging
Charging Time	<2hours
APP OS	
iOS	IOS 12.0+
Android	Android6.0+
Function 功能	
Language (General)	English、Chinese、German、Spanish、French、Italian、Japanese、Russian、Portuguese、Polish、turkish、vietnamese、Indonesia、Dutch、Greek、Czech default: English
Basic Functions	Clock, Date Display 12/24H
	Multi-watch face Online 100+ & DIY
	OTA Upgrade
BT Call	Contacts
	Call records
	Dial
Daily activity monitoring	Heart rate
	Sleep monitor
	Steps
	Calories
	Distance
	wear detection
Exercise Functions-16	Outdoor Running
	Outdoor Walking
	Outdoor Cycling
	Indoor Running
	power Training
	Football
	Basketball
	Volleyball
	Badminton
	Rope Skipping
	Row boating
	Elliptical
	Swimming
	Yoga
	Hiking
	Free Tranning
	110+ sport modes support
Auto monitoring	Heart rate (Auto)
	Blood Oxygen (Auto)
	Incoming call

Reminder	SMS notification
	low battery
	Alarm Clock
	Activity reminder
	Drink water reminder
	Target reaching Reminder
	High Heart rate when doing Exercise
	Women's Health
	Connecting reminder
Other functions	Breath Training
	Weather forecast
	Music Control
	Stopwatch
	Alarm
	Timer
	Flashlight
	Find phone
	Ringtone setting
	Menu style
	Restore factory settings
	Scan QR code to binding
	Set the screen duration
	Firmware information
Gesture	Lift the wrist
	Lower the wrist
Environmental	
Working Temperature	-20°C to 50°C
Charge Temperature	0°C to 40°C
Working Humidity	10%-90%RH
Storage Temperature	-30°C to 70°C
Storage Humidity	5%-90%RH