



3" Thermal POS Receipt Printer HCC-POS80B

Feature

1. Extremely compact and smart design;
2. Flexible placement, front and upside paper exit;
3. Innovative structure to ensure cutter jam free;
4. Easy paper loading, Easy operation and maintenance;
5. High speed at 250/300mm/s;
6. Printing space saving to reduce paper cost;
7. Support 58/80mm paper width;
8. LED directly shows printer status;
9. Various interfaces USB/Serial/Ethernet/Bluetooth/wifi/Cloud for option;
10. Support various Windows OS, Linux and OPOS driver;
11. Compatible with ESC/POS command
12. Support Windows/Android/IOS DEMO&SDK

Specification

Print Method	Direct thermal line
Print Speed	250MM/S(default) 300MM/S(max.)
Effective Print Width	72mm
Font	Dot Density: 576 dot/ line(max.) Character Size ANK Character Font A: 12*24, Font B: 9*17, 24*24 Barcode 1-D:UPCA/UPCE/JAN13(EAN13)/JAN8(EAN8/CODE39/ITF/CO DABAR/CODE93/CODE128 2-D: QR Code, PDF417
Print Paper	Paper Type: Thermal paper Paper Width: 57.5±0.5mm/79.5±0.5mm Outer Diameter: 83mm(max.) Paper Thickness: 0.06~0.08mm Loading Method: Drop-in easy paper loading
Reliability	Print Head: 100km Auto Cutter: 1,500,000 times
Print Command	Compatible with ESC/POS
Driver	Win9X/Win ME/Win2000/Win NT/Win XP/Win Vista/Win7/Linux/OPOS/Android/IOS
Interface	Serial+USB/Serial+USB+Ethernet/Serial+USB+Bluetooth/Serial +USB+WiFi/ Serial+ USB+ WiFi(cloud)
Power Adaptor	DC 24V/2A

Cash Drawer Power	DC 24V/2A
Auto Cutter	Full or Partial Cut
Physical parameters	Net Weight: 1.2kg (without paper roll) Dimension: 127*127*129mm Color: Black/white
Operating Temp	0~50°C
Storage Temp	-20-60°C
Operating Humidity	10~80%
Storage Humidity	10%-90% (No condensation)

Picture

